ISO 20950-1:2018 (E)

Water quality — Determination of available weak and dissociable (WAD) cyanide — Part 1: Method using ligand exchange, flow injection analysis (FIA), gas-diffusion and amperometric detection

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Interferences

4.1 Interferences by oxidizing agents
4.2 Interferences by sulfide

5 Principle

6 Reagents

7 Apparatus

8 Sampling and sample preparation

8.1 General
8.2 Oxidizing agents
8.3 Sulfide removal
8.4 Preservation

9 Procedure

9.1 Flow system set up
9.2 Reagent blank measurement
9.3 Checking the suitability of the flow injection system
9.3.1 Cyanide electrode stabilization
9.3.2 Performance verification of the system
9.4 Calibration
9.5 Sample measurement
9.5.1 General
9.5.2 Manual ligand addition options
9.5.2.1 General
9.5.2.2 Ligand exchange reagent A and B option
9.5.2.3 Ligand exchange reagent 1 and 2 option
9.5.3 Automated ligand addition
9.5.4 Cyanide measurement

10 Calculations

11 Expression of results

12 Test report

Annex A (informative) Examples of flow injection systems

Annex B (normative) Determination of the real cyanide concentration in the potassium cyanide solution (6.5.1) or potassium tetracyanozincate solution (6.6.1)

B.1 General
B.2 Additional reagents
B.3 Determination of cyanide concentration in potassium cyanide solution (6.5.1)

Annex C (informative) Performance data

Page count: 17