

# ISO 9912-4:2018 (E)

## Agricultural irrigation equipment — Filters for microirrigation — Part 4: Granulated media filters

---

### Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Design and construction requirements
4.1	General
4.2	Inlet and expansion space chamber
4.3	Media chamber
4.4	Collection (underdrain) and back flushing unit
4.5	Prefiltration element
4.6	Back flushing control
4.6.1	Mandatory requirements
4.6.2	Optional features
5	Resistance of the filter to internal hydrostatic pressure
5.1	General
5.2	Preparation
5.3	Static pressure test
5.4	Cyclic pressure test
5.5	Collection (underdrain) and back flushing unit resistance to buckling or tearing
6	Clean pressure drop test
6.1	General
6.2	Flow rates and test sequence
6.3	Filter media
6.4	Prescreening
6.5	Inlet and outlet pressures
6.6	Test duration
6.7	Report
7	Back flushing tests
7.1	Back flushing parameters
7.2	Media escape test
8	Automatic back flushing and controller
8.1	Back flushing initiation
8.2	Flushing control mechanism test
8.2.1	Mechanism activated by pressure drop
8.2.2	Mechanism activated by duration of operation
8.2.3	Mechanism activated by volume of filtered water
8.2.4	Mechanism activated by another physical quantity
8.3	Operation of the protective device
9	Information to be supplied by the manufacturer
9.1	General
9.2	Filter data
9.3	Back flushing controller
Annex A	(informative) Types of irrigation media filters

**Annex B (informative) Granulated media**

- B.1 General**
- B.2 Rough media classification**
  - B.2.1 General**
  - B.2.2 Grain size and particle size distribution**
  - B.2.3 Other common guidelines**
- B.3 Maintenance**

**Page count: 16**