

ISO 11296-7:2019 (E)

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks — Part 7: Lining with spirally-wound pipes

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Pipes at the “M” stage
5.1	Materials
5.2	General characteristics
5.3	Material characteristics
5.4	Geometric characteristics
5.5	Mechanical characteristics
5.6	Physical characteristics
5.7	Jointing
5.8	Marking
6	Fittings at the “M” stage
7	Ancillary components
8	Fitness for purpose of the installed lining system at the “I” stage
8.1	Materials
8.2	General characteristics
8.3	Material characteristics
8.4	Geometric characteristics
8.5	Mechanical characteristics
8.6	Physical characteristics
8.7	Additional characteristics
8.8	Preparation of samples
8.9	Adhesives
9	Installation practice
9.1	Preparatory work
9.2	Storage, handling and transportation of profiled plastics strips and fittings
9.3	Equipment
9.4	Installation
9.5	Process-related inspection and testing
9.6	Lining termination
9.7	Reconnecting to existing manholes and laterals
9.8	Final inspection and testing
9.9	Documentation
Annex A	(normative) Spirally-wound pipe — Test method for watertightness in a deflected condition
A.1	Scope
A.2	Principle

- A.3 Apparatus
- A.4 Sample
- A.5 Test procedure
- A.6 Test report

Annex B (informative) Examples of methods for reconnecting and sealing laterals to SWO pipe

Page count: 16