DIN EN 12457-3:2021-03 (E)

Characterization of waste - Leaching - Compliance test for leaching of granular waste materials and sludges - Part 3: Two stage batch test at a liquid to solid ratio of 2 l/kg and 8 l/kg for materials with high solid content with particle size below 4 mm (wit hout or with size reduction)

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7
3.1 leaching test 7
3.2 leachant 7
3.3 eluate 7
3.4 single batch leaching test 7
3.5 serial batch leaching test 7
3.6 liquid to solid ratio L/S (abbreviation : L/S) 7
3.7 liquid waste 7
3.8 sludge 7
3.9 monolithic waste 7
3.10 granular waste 7
3.11 dry matter content ratio (abbreviation : DR) 7
3.12 moisture content ratio (abbreviation MC) 8
3.13 laboratory sample 8
3.14 test sample 8
3.15 test portion 8

4 Compliance test 8
4.1 Principle 8
4.2 Equipment and reagents 8
4.3 Sampling strategy and sample preparation 9

5 Procedure 11
5.1 Testing conditions 11
5.2 Description of the procedure 11
5.3 Further preparation of the eluates for analysis 13
5.4 Blank test for the verification of the leaching procedure 13

6 Calculation 13
6.1 Expression of the results 13
6.2 First step batch at L/S = 2 14
6.3 Second step batch at L/S = 8 14

7 Documentation and test report 14
7.1 Sample preparation 14
7.2 Production of eluate 15
7.3 Analytical determination 15
7.4 Calculations and blank test information 16

8 Performance characteristics 16

8.1 Objective of the validation 16
8.2 Validation study 16
8.3 Validation results 17
8.4 Summary of the performance characteristics evaluation 20

Annex A(informative) Information on the influence on the test results of the parameters that affect leaching 22

Annex B(informative) Test for determining whether waste is in the liquid state 24

Annex E(informative) Example of a specific liquid-solid separation procedure for soil sample 28

Annex ZA (Informative) National deviation A from France 29

Bibliography 30