

ISO 3455:2021 (E)

Hydrometry — Calibration of current-meters in straight open tanks

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Principle of calibration
4.1	Statement of the principle
4.2	Accuracy of the method
4.2.1	Overall uncertainty on the velocity measurement
4.2.2	Requirements for accurate measurements
5	Infrastructure
5.1	Dimensions of the towing tank
5.1.1	General
5.1.2	Length
5.1.3	Depth and width
5.2	Towing cart
5.2.1	General
5.2.2	Cart track system
5.2.3	Types of towing carts
5.2.4	Cart operation
5.2.5	Cart control
5.3	Measuring equipment
5.3.1	General
5.3.2	Distance measurement
5.3.3	Time measurement
5.3.4	Current-meter velocity measurement
5.3.5	Sources of error related to infrastructure
5.3.5.1	General
5.3.5.2	Error due to the distance measurement
5.3.5.3	Error due to timing measurement
5.3.5.4	Error due to residual currents in the water
5.3.5.5	Error due to environmental conditions
5.3.5.6	Random errors
5.4	Data acquisition
5.5	Data processing
5.6	Other requirements
6	Calculation of uncertainty
7	Calibration procedure
7.1	Calibration of rotating element current-meters
7.1.1	Suspension of the current-meter
7.1.2	Performance of calibration
7.1.2.1	Minimum speed of response
7.1.2.2	Number of calibration points
7.1.2.3	Stilling time
7.1.3	Data analysis
7.1.3.1	Velocity v and the rotation rate n
7.1.3.2	Determination of outliers
7.1.3.3	Calibration formulae
7.1.4	Presentation of results

7.2	Calibration of electromagnetic current-meters
7.2.1	Instructions for calibration
7.2.2	Mounting the electromagnetic current-meter
7.2.3	Number of calibration points
7.2.4	Performance of calibration
7.2.5	Data analysis
7.2.6	Presentation of results
7.3	Calibration of acoustic current-meters for point velocity measurement
7.3.1	Instructions for calibration
7.3.2	Mounting the acoustic current-meter
7.3.3	Performance of calibration
7.3.3.1	Number of calibration points
7.3.3.2	Stilling time
7.3.4	Data analysis
7.3.5	Presentation of results

Page count: 13