

ISO 21052:2021-11 (E)

Restrained joint systems for ductile iron pipelines - Calculation rules for lengths to be restrained

| Contents | Page |
|---|-----------|
| Foreword | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms, definitions and symbols | 1 |
| 3.1 Terms and definitions | 1 |
| 3.2 Symbols | 3 |
| 4 Thrust restraint principles, calculation rules and general specification | 4 |
| 4.1 Thrust forces | 4 |
| 4.2 Calculation rules and general specification | 4 |
| 4.3 Standard jointing systems offer no longitudinal restraint | 5 |
| 4.4 Restrained joint systems | 5 |
| 4.5 Length to be restrained | 5 |
| 4.6 Restrained design method | 5 |
| 4.7 Gravity thrust blocks | 6 |
| 5 Thrust force | 6 |
| 5.1 Internal hydrostatic pressure in straight pipes | 6 |
| 5.2 Internal hydrostatic pressure in bends | 6 |
| 5.3 Internal hydrostatic pressure in other configurations | 7 |
| 6 Restrained joints | 8 |
| 6.1 Principle | 8 |
| 6.2 Conservative design | 8 |
| 6.3 Required prevailing site conditions | 8 |
| 7 Unit frictional force, F_s | 8 |
| 7.1 Static frictional force | 8 |
| 7.2 Values of soil cohesion | 9 |
| 8 Polyethylene encasement and PU coating and other extruded organic coatings | 10 |
| 9 Unit bearing resistances, R_s | 10 |
| 9.1 Lateral resistance, passive soil pressure | 10 |
| 9.2 Design value of passive soil pressure | 10 |
| 9.3 Empirical values of passive soil pressure | 11 |
| 10 Application to common situations | 14 |
| 10.1 Horizontal bends | 14 |
| 10.2 Vertical down bends | 15 |
| 10.3 Vertical up bends | 15 |
| 10.4 Tees | 16 |
| 10.5 Reducers | 17 |
| 10.6 Dead ends | 17 |
| 10.7 Encroaching restrained lengths | 17 |
| 10.8 Equal angle vertical offset (θ) | 18 |
| 10.9 Combined horizontal equal angle bends (θ) | 19 |
| 10.10 Combined horizontal unequal angle bends | 20 |
| 10.11 Combined vertical equal angle offsets (θ) | 21 |
| 10.11.1 Pipeline under obstruction | 21 |
| 10.11.2 Pipeline over obstruction | 22 |
| 11 Restrainted lengths | 22 |

| | | |
|--|--|-----------|
| 12 | Installation and laying instruction | 22 |
| 12.1 | Select backfill considerations..... | 22 |
| 12.1.1 | Backfill material versus native soil support characteristics..... | 22 |
| 12.1.2 | Swamps or marshes..... | 22 |
| 12.2 | Combining thrust blocks/anchor blocks and restrained joints | 22 |
| 12.3 | Pipe in a casing..... | 23 |
| 12.3.1 | Restrained lengths inside casing..... | 23 |
| 12.3.2 | Balancing the thrust force with restraining lengths outside the casing | 23 |
| 12.4 | Future excavations | 23 |
| Annex A (informative) Dimensions and unit weights of pipes filled with water for preferred class..... | 24 | |
| Annex B (informative) Soil classification chart..... | 25 | |
| Bibliography..... | 26 | |