

DIN EN ISO 13165-2:2024-12 (E)

Water quality - Radium-226 - Part 2: Test method using emanometry (ISO 13165-2:2022)

| Contents | | Page |
|---|-------|-------------|
| European foreword | | 3 |
| Foreword | | 4 |
| Introduction | | 5 |
| 1 Scope | | 7 |
| 2 Normative references | | 7 |
| 3 Terms, definitions and symbols | | 7 |
| 3.1 Terms and definitions | | 7 |
| 3.2 Symbols | | 8 |
| 4 Principle | | 9 |
| 5 Reagents and equipment | | 10 |
| 5.1 Reagents | | 10 |
| 5.2 Equipment | | 10 |
| 6 Sampling and storage | | 10 |
| 6.1 Sampling | | 10 |
| 6.2 Sample storage | | 11 |
| 7 Procedures | | 11 |
| 7.1 Sample preparation | | 11 |
| 7.2 Measurement conditions | | 11 |
| 7.3 Counting procedure | | 12 |
| 8 Quality assurance and quality control programme | | 12 |
| 8.1 General | | 12 |
| 8.2 Influence parameters | | 12 |
| 8.3 Instrument verification and calibration | | 12 |
| 8.4 Method verification | | 13 |
| 8.5 Demonstration of analyst capability | | 13 |
| 9 Expression of results | | 13 |
| 9.1 Activity concentration of water-soluble ²²⁶ Ra | | 13 |
| 9.2 Standard uncertainty of activity concentration | | 14 |
| 9.2.1 General | | 14 |
| 9.2.2 Decision threshold | | 14 |
| 9.2.3 Detection limit | | 14 |
| 9.3 Limits of the coverage intervals | | 15 |
| 9.3.1 Limits of the probabilistically symmetric coverage interval | | 15 |
| 9.3.2 Shortest coverage interval | | 15 |
| 9.4 Example | | 15 |
| 10 Test report | | 16 |
| Annex A (informative) Decay chains of ²³⁸U and ²³²Th | | 18 |
| Annex B (informative) Bubbler | | 20 |
| Annex C (informative) Glass scintillation cell coated with silver-activated zinc sulfide | | 21 |
| Bibliography | | 22 |