

# DIN EN 14758-1:2023-11 (E)

## Plastics piping systems for non-pressure underground drainage and sewerage - Polypropylene with mineral modifiers (PP-MD) - Part 1: Specifications for pipes, fittings and the system

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>8</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>12</b>
<b>4.1</b>	<b>Symbols .....</b>	<b>12</b>
<b>4.2</b>	<b>Abbreviations .....</b>	<b>12</b>
<b>5</b>	<b>Material .....</b>	<b>13</b>
<b>5.1</b>	<b>PP-MD compound .....</b>	<b>13</b>
<b>5.2</b>	<b>PP compound for the skin .....</b>	<b>13</b>
<b>5.3</b>	<b>Utilization of reworked material and recyclate .....</b>	<b>13</b>
<b>5.4</b>	<b>Melt mass-flow rate .....</b>	<b>13</b>
<b>5.5</b>	<b>Fusion compatibility of fabricated fittings .....</b>	<b>13</b>
<b>5.6</b>	<b>Mineral modifiers .....</b>	<b>13</b>
<b>5.6.1</b>	<b>Types of mineral modifiers .....</b>	<b>13</b>
<b>5.6.2</b>	<b>Characteristics of mineral modifiers .....</b>	<b>14</b>
<b>5.6.3</b>	<b>Dispersion of mineral modifiers .....</b>	<b>14</b>
<b>5.7</b>	<b>Long-term behaviour .....</b>	<b>14</b>
<b>5.8</b>	<b>Thermal stability (OIT) .....</b>	<b>15</b>
<b>5.9</b>	<b>Sealing ring retaining means .....</b>	<b>15</b>
<b>6</b>	<b>General characteristics .....</b>	<b>15</b>
<b>6.1</b>	<b>Appearance .....</b>	<b>15</b>
<b>6.2</b>	<b>Colour .....</b>	<b>15</b>
<b>7</b>	<b>Geometrical characteristics .....</b>	<b>16</b>
<b>7.1</b>	<b>General .....</b>	<b>16</b>
<b>7.2</b>	<b>Dimensions of pipes .....</b>	<b>16</b>
<b>7.2.1</b>	<b>Outside diameters .....</b>	<b>16</b>
<b>7.2.2</b>	<b>Outside diameters with close tolerance (type CT) .....</b>	<b>17</b>
<b>7.2.3</b>	<b>Minimum mean inside diameter .....</b>	<b>17</b>
<b>7.2.4</b>	<b>Length of pipes .....</b>	<b>17</b>
<b>7.2.5</b>	<b>Chamfering .....</b>	<b>18</b>
<b>7.2.6</b>	<b>Wall thicknesses .....</b>	<b>18</b>
<b>7.3</b>	<b>Ring stiffness classes .....</b>	<b>19</b>
<b>7.4</b>	<b>Dimensions of fittings .....</b>	<b>19</b>
<b>7.4.1</b>	<b>Outside diameters .....</b>	<b>19</b>
<b>7.4.2</b>	<b>Design lengths .....</b>	<b>19</b>
<b>7.4.3</b>	<b>Wall thicknesses and stiffness .....</b>	<b>19</b>
<b>7.5</b>	<b>Dimensions of sockets and spigots .....</b>	<b>20</b>
<b>7.5.1</b>	<b>Diameters and lengths of elastomeric ring seal sockets and spigots .....</b>	<b>20</b>
<b>7.5.2</b>	<b>Wall thicknesses of sockets .....</b>	<b>23</b>
<b>7.6</b>	<b>Types of fittings .....</b>	<b>23</b>

<b>8</b>	<b>Mechanical characteristics</b> .....	<b>27</b>
<b>8.1</b>	<b>Mechanical characteristics of pipes</b> .....	<b>27</b>
<b>8.1.1</b>	<b>General requirements</b> .....	<b>27</b>
<b>8.1.2</b>	<b>Ring flexibility</b> .....	<b>28</b>
<b>8.1.3</b>	<b>Additional mechanical requirements</b> .....	<b>29</b>
<b>8.2</b>	<b>Mechanical characteristics of fittings</b> .....	<b>29</b>
<b>9</b>	<b>Physical characteristics</b> .....	<b>30</b>
<b>9.1</b>	<b>Physical characteristics of pipes</b> .....	<b>30</b>
<b>9.2</b>	<b>Physical characteristics of fittings</b> .....	<b>31</b>
<b>10</b>	<b>Performance requirements</b> .....	<b>31</b>
<b>11</b>	<b>Sealing rings</b> .....	<b>32</b>
<b>12</b>	<b>Marking</b> .....	<b>32</b>
<b>12.1</b>	<b>General</b> .....	<b>32</b>
<b>12.2</b>	<b>Minimum required marking of pipes</b> .....	<b>33</b>
<b>12.3</b>	<b>Minimum required marking of fittings</b> .....	<b>33</b>
<b>12.4</b>	<b>Additional marking</b> .....	<b>34</b>
<b>Annex A (normative) Utilization of reworked material and recyclate</b> .....		<b>35</b>
<b>A.1</b>	<b>Reworked material</b> .....	<b>35</b>
<b>A.2</b>	<b>Pre-consumer materials</b> .....	<b>35</b>
<b>A.3</b>	<b>Post-consumer materials from pipes and fittings</b> .....	<b>36</b>
<b>A.4</b>	<b>Post-consumer materials from other products than pipes and fittings</b> .....	<b>36</b>
<b>A.5</b>	<b>Additional specifications for the agreed specification</b> .....	<b>36</b>
<b>Annex B (informative) General characteristics of PP-MD pipes and fittings</b> .....		<b>37</b>
<b>B.1</b>	<b>General</b> .....	<b>37</b>
<b>B.2</b>	<b>Material characteristics</b> .....	<b>37</b>
<b>B.3</b>	<b>Ring stiffness</b> .....	<b>37</b>
<b>B.4</b>	<b>Chemical resistance</b> .....	<b>38</b>
<b>B.5</b>	<b>Abrasion resistance</b> .....	<b>38</b>
<b>B.6</b>	<b>Hydraulic roughness</b> .....	<b>38</b>
<b>B.7</b>	<b>Diametric deflection</b> .....	<b>38</b>
<b>Annex C (informative) Product standards of components that can be connected to components conforming to this document</b> .....		<b>39</b>
<b>Annex D (informative) Testing PP recyclates with the CRB-method</b> .....		<b>40</b>
<b>D.1</b>	<b>General</b> .....	<b>40</b>
<b>D.2</b>	<b>Principle</b> .....	<b>40</b>
<b>D.3</b>	<b>Procedure</b> .....	<b>40</b>
<b>D.3.1</b>	<b>Sample preparation</b> .....	<b>40</b>
<b>D.3.2</b>	<b>CRB failure curve</b> .....	<b>41</b>
<b>D.3.3</b>	<b>PP test parameters</b> .....	<b>41</b>
<b>D.3.4</b>	<b>Verification procedure</b> .....	<b>41</b>
<b>Bibliography</b> .....		<b>44</b>