

# DIN EN 14758-1:2023-11 (E)

## Plastics piping systems for non-pressure underground drainage and sewerage - Polypropylene with mineral modifiers (PP-MD) - Part 1: Specifications for pipes, fittings and the system

---

| <b>Contents</b>         |   | <b>Page</b> |
|-------------------------|---|-------------|
| European foreword ..... |   | 4           |
| <b>1</b>                | <b>Scope .....</b>  | <b>6</b>    |
| <b>2</b>                | <b>Normative references .....</b>   | <b>6</b>    |
| <b>3</b>                | <b>Terms and definitions .....</b>  | <b>8</b>    |
| <b>4</b>                | <b>Symbols and abbreviations .....</b>  | <b>12</b>   |
| <b>4.1</b>              | <b>Symbols .....</b>  | <b>12</b>   |
| <b>4.2</b>              | <b>Abbreviations .....</b>  | <b>12</b>   |
| <b>5</b>                | <b>Material .....</b>   | <b>13</b>   |
| <b>5.1</b>              | <b>PP-MD compound .....</b>   | <b>13</b>   |
| <b>5.2</b>              | <b>PP compound for the skin .....</b>   | <b>13</b>   |
| <b>5.3</b>              | <b>Utilization of reworked material and recyclate .....</b>                     | <b>13</b>   |
| <b>5.4</b>              | <b>Melt mass-flow rate .....</b>  | <b>13</b>   |
| <b>5.5</b>              | <b>Fusion compatibility of fabricated fittings .....</b>                        | <b>13</b>   |
| <b>5.6</b>              | <b>Mineral modifiers .....</b>  | <b>13</b>   |
| <b>5.6.1</b>            | <b>Types of mineral modifiers .....</b>   | <b>13</b>   |
| <b>5.6.2</b>            | <b>Characteristics of mineral modifiers .....</b>                               | <b>14</b>   |
| <b>5.6.3</b>            | <b>Dispersion of mineral modifiers .....</b>                                    | <b>14</b>   |
| <b>5.7</b>              | <b>Long-term behaviour .....</b>  | <b>14</b>   |
| <b>5.8</b>              | <b>Thermal stability (OIT) .....</b>  | <b>15</b>   |
| <b>5.9</b>              | <b>Sealing ring retaining means .....</b>                                       | <b>15</b>   |
| <b>6</b>                | <b>General characteristics .....</b>  | <b>15</b>   |
| <b>6.1</b>              | <b>Appearance .....</b>   | <b>15</b>   |
| <b>6.2</b>              | <b>Colour .....</b>   | <b>15</b>   |
| <b>7</b>                | <b>Geometrical characteristics .....</b>  | <b>16</b>   |
| <b>7.1</b>              | <b>General .....</b>  | <b>16</b>   |
| <b>7.2</b>              | <b>Dimensions of pipes .....</b>  | <b>16</b>   |
| <b>7.2.1</b>            | <b>Outside diameters .....</b>  | <b>16</b>   |
| <b>7.2.2</b>            | <b>Outside diameters with close tolerance (type CT) .....</b>                   | <b>17</b>   |
| <b>7.2.3</b>            | <b>Minimum mean inside diameter .....</b>                                       | <b>17</b>   |
| <b>7.2.4</b>            | <b>Length of pipes .....</b>  | <b>17</b>   |
| <b>7.2.5</b>            | <b>Chamfering .....</b>   | <b>18</b>   |
| <b>7.2.6</b>            | <b>Wall thicknesses .....</b>   | <b>18</b>   |
| <b>7.3</b>              | <b>Ring stiffness classes .....</b>   | <b>19</b>   |
| <b>7.4</b>              | <b>Dimensions of fittings .....</b>   | <b>19</b>   |
| <b>7.4.1</b>            | <b>Outside diameters .....</b>  | <b>19</b>   |
| <b>7.4.2</b>            | <b>Design lengths .....</b>   | <b>19</b>   |
| <b>7.4.3</b>            | <b>Wall thicknesses and stiffness .....</b>                                     | <b>19</b>   |
| <b>7.5</b>              | <b>Dimensions of sockets and spigots .....</b>                                  | <b>20</b>   |
| <b>7.5.1</b>            | <b>Diameters and lengths of elastomeric ring seal sockets and spigots .....</b> | <b>20</b>   |
| <b>7.5.2</b>            | <b>Wall thicknesses of sockets .....</b>  | <b>23</b>   |
| <b>7.6</b>              | <b>Types of fittings .....</b>  | <b>23</b>   |

|  |  |           |
|--|--|-----------|
| <b>8</b>   | <b>Mechanical characteristics .....</b>  | <b>27</b> |
| <b>8.1</b>   | <b>Mechanical characteristics of pipes .....</b>                                 | <b>27</b> |
| <b>8.1.1</b>   | <b>General requirements .....</b>  | <b>27</b> |
| <b>8.1.2</b>   | <b>Ring flexibility .....</b>  | <b>28</b> |
| <b>8.1.3</b>   | <b>Additional mechanical requirements .....</b>                                  | <b>29</b> |
| <b>8.2</b>   | <b>Mechanical characteristics of fittings .....</b>                              | <b>29</b> |
| <b>9</b>   | <b>Physical characteristics .....</b>  | <b>30</b> |
| <b>9.1</b>   | <b>Physical characteristics of pipes .....</b>                                   | <b>30</b> |
| <b>9.2</b>   | <b>Physical characteristics of fittings .....</b>                                | <b>31</b> |
| <b>10</b>  | <b>Performance requirements .....</b>  | <b>31</b> |
| <b>11</b>  | <b>Sealing rings .....</b>   | <b>32</b> |
| <b>12</b>  | <b>Marking .....</b>   | <b>32</b> |
| <b>12.1</b>  | <b>General .....</b>   | <b>32</b> |
| <b>12.2</b>  | <b>Minimum required marking of pipes .....</b>                                   | <b>33</b> |
| <b>12.3</b>  | <b>Minimum required marking of fittings .....</b>                                | <b>33</b> |
| <b>12.4</b>  | <b>Additional marking .....</b>  | <b>34</b> |
| <b>Annex A (normative) Utilization of reworked material and recyclate .....</b>  |  | <b>35</b> |
| <b>A.1</b>   | <b>Reworked material .....</b>   | <b>35</b> |
| <b>A.2</b>   | <b>Pre-consumer materials .....</b>  | <b>35</b> |
| <b>A.3</b>   | <b>Post-consumer materials from pipes and fittings .....</b>                     | <b>36</b> |
| <b>A.4</b>   | <b>Post-consumer materials from other products than pipes and fittings .....</b> | <b>36</b> |
| <b>A.5</b>   | <b>Additional specifications for the agreed specification .....</b>              | <b>36</b> |
| <b>Annex B (informative) General characteristics of PP-MD pipes and fittings .....</b>   |  | <b>37</b> |
| <b>B.1</b>   | <b>General .....</b>   | <b>37</b> |
| <b>B.2</b>   | <b>Material characteristics .....</b>  | <b>37</b> |
| <b>B.3</b>   | <b>Ring stiffness .....</b>  | <b>37</b> |
| <b>B.4</b>   | <b>Chemical resistance .....</b>   | <b>38</b> |
| <b>B.5</b>   | <b>Abrasion resistance .....</b>   | <b>38</b> |
| <b>B.6</b>   | <b>Hydraulic roughness .....</b>   | <b>38</b> |
| <b>B.7</b>   | <b>Diametric deflection .....</b>  | <b>38</b> |
| <b>Annex C (informative) Product standards of components that can be connected to components conforming to this document .....</b> |  | <b>39</b> |
| <b>Annex D (informative) Testing PP recyclates with the CRB-method .....</b>   |  | <b>40</b> |
| <b>D.1</b>   | <b>General .....</b>   | <b>40</b> |
| <b>D.2</b>   | <b>Principle .....</b>   | <b>40</b> |
| <b>D.3</b>   | <b>Procedure .....</b>   | <b>40</b> |
| <b>D.3.1</b>   | <b>Sample preparation .....</b>  | <b>40</b> |
| <b>D.3.2</b>   | <b>CRB failure curve .....</b>   | <b>41</b> |
| <b>D.3.3</b>   | <b>PP test parameters .....</b>  | <b>41</b> |
| <b>D.3.4</b>   | <b>Verification procedure .....</b>  | <b>41</b> |
| <b>Bibliography .....</b>  |  | <b>44</b> |