ISO/TS 16422-3:2023-06 (E)

Pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for the conveyance of water under pressure - Part 3: Fittings

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **2**

4 Symbols ... **3**

5 Material ... **5**
5.1 General ... 5
5.2 Density ... 5
5.3 Orientation factor ... 5

6 General characteristics ... **5**
6.1 Appearance ... 5
6.2 Colour ... 5
6.3 Opacity ... 6
6.4 Classification of fittings ... 6

7 Geometrical characteristics ... **6**
7.1 Design lengths, bend radii and angles ... 6
7.2 Measurement of dimensions ... 6
7.3 Nominal outside diameters and wall thickness ... 6
7.4 Fittings with integral sockets with elastomeric sealing ring type ... 6

8 Pressure and operating temperature ... **7**
8.1 Selection of nominal pressure for water up to and including 25 °C ... 7
8.2 Determination of the allowable operating pressure for water up to 45 °C ... 7

9 Mechanical characteristics — Resistance to hydrostatic pressure ... **7**

10 Physical characteristics ... **7**

11 Sealing rings ... **8**

12 Performance requirements ... **8**

13 Marking ... **8**
13.1 General ... 8
13.2 Minimum required marking ... 8
13.3 Additional marking ... 9

Annex A (normative) **Determination of long-term hydrostatic strength** ... **10**

Annex B (normative) **Determination of circumferential orientation factor** ... **12**

Annex C (informative) **Recommended dimensions of PVC-O fittings** ... **14**

Bibliography ... **19**