

# ISO/TS 16422-3:2023-06 (E)

## Pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for the conveyance of water under pressure - Part 3: Fittings

---

<b>Contents</b>	<b>Page</b>
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Symbols</b> .....	<b>3</b>
<b>5 Material</b> .....	<b>5</b>
5.1 General.....	5
5.2 Density.....	5
5.3 Orientation factor.....	5
<b>6 General characteristics</b> .....	<b>5</b>
6.1 Appearance.....	5
6.2 Colour.....	5
6.3 Opacity.....	6
6.4 Classification of fittings.....	6
<b>7 Geometrical characteristics</b> .....	<b>6</b>
7.1 Design lengths, bend radii and angles.....	6
7.2 Measurement of dimensions.....	6
7.3 Nominal outside diameters and wall thickness.....	6
7.4 Fittings with integral sockets with elastomeric sealing ring type.....	6
<b>8 Pressure and operating temperature</b> .....	<b>7</b>
8.1 Selection of nominal pressure for water up to and including 25 °C.....	7
8.2 Determination of the allowable operating pressure for water up to 45 °C.....	7
<b>9 Mechanical characteristics — Resistance to hydrostatic pressure</b> .....	<b>7</b>
<b>10 Physical characteristics</b> .....	<b>7</b>
<b>11 Sealing rings</b> .....	<b>8</b>
<b>12 Performance requirements</b> .....	<b>8</b>
<b>13 Marking</b> .....	<b>8</b>
13.1 General.....	8
13.2 Minimum required marking.....	8
13.3 Additional marking.....	9
<b>Annex A (normative) Determination of long-term hydrostatic strength</b> .....	<b>10</b>
<b>Annex B (normative) Determination of circumferential orientation factor</b> .....	<b>12</b>
<b>Annex C (informative) Recommended dimensions of PVC-O fittings</b> .....	<b>14</b>
<b>Bibliography</b> .....	<b>19</b>