

ISO 27913:2024-10 (E)

Carbon dioxide capture, transportation and geological storage - Pipeline transportation systems

Contents

Page

| | |
|--|----------|
| Foreword..... | vi |
| Introduction..... | vii |
| 1 Scope..... | 1 |
| 2 Normative references..... | 1 |
| 3 Terms and definitions..... | 1 |
| 4 Symbols and abbreviated terms..... | 5 |
| 4.1 Symbols..... | 5 |
| 4.2 Abbreviated terms..... | 5 |
| 5 Properties of CO₂, CO₂ streams and the mixing of CO₂ streams that influence pipeline transportation..... | 6 |
| 5.1 General..... | 6 |
| 5.2 Pure CO ₂ | 6 |
| 5.2.1 Thermodynamics..... | 6 |
| 5.2.2 Chemical reactions and corrosion..... | 6 |
| 5.3 CO ₂ streams..... | 7 |
| 5.3.1 Thermodynamics..... | 7 |
| 5.3.2 Chemical reactions..... | 7 |
| 6 Concept development and design criteria..... | 7 |
| 6.1 General..... | 7 |
| 6.2 Safety philosophy..... | 7 |
| 6.3 Reliability and availability of CO ₂ stream pipeline systems..... | 8 |
| 6.4 Short-term storage reserve..... | 8 |
| 6.5 Access to the pipeline system..... | 8 |
| 6.6 System design principles..... | 9 |
| 6.6.1 General..... | 9 |
| 6.6.2 CO ₂ stream specification..... | 9 |
| 6.6.3 Pressure control and protection system..... | 10 |
| 6.7 General principles to avoid internal pipeline corrosion..... | 10 |
| 6.7.1 Particular aspects related to CO ₂ streams..... | 10 |
| 6.7.2 Maximum water content..... | 10 |
| 6.7.3 Avoidance of hydrate formation..... | 10 |
| 6.7.4 Measurement of water content in the CO ₂ stream..... | 11 |
| 6.8 Flow assurance..... | 11 |
| 6.8.1 General..... | 11 |
| 6.8.2 Operation under single-phase flow conditions during normal operation..... | 11 |
| 6.8.3 Pipeline operation under multi-phase flow conditions during transient operations..... | 12 |
| 6.8.4 Planned and unscheduled pipeline pressure release..... | 12 |
| 6.8.5 Reduced flow capacity..... | 13 |
| 6.8.6 Available transport capacity..... | 13 |
| 6.8.7 Flow coating..... | 13 |
| 6.8.8 External thermal insulation..... | 14 |
| 6.8.9 Leak detection..... | 14 |
| 6.8.10 Fugitive emissions..... | 14 |
| 6.8.11 Impurities..... | 14 |
| 6.9 Pipeline layout..... | 14 |
| 6.9.1 Vent stations..... | 14 |

| | | |
|-----------|---|-----------|
| 6.9.2 | Block valve stations..... | 15 |
| 6.9.3 | Pumping and compressor stations..... | 15 |
| 6.9.4 | In-line inspection..... | 15 |
| 6.9.5 | Onshore vent facility design..... | 15 |
| 6.9.6 | Offshore vent facilities..... | 16 |
| 7 | Materials and pipeline design..... | 16 |
| 7.1 | General..... | 16 |
| 7.2 | Internal corrosion..... | 16 |
| 7.3 | Pipeline system materials..... | 17 |
| 7.3.1 | Steel selection..... | 17 |
| 7.3.2 | External coating..... | 17 |
| 7.3.3 | Non-metallic materials..... | 17 |
| 7.3.4 | Lubricants..... | 17 |
| 8 | Wall thickness calculations..... | 18 |
| 8.1 | Calculation principles..... | 18 |
| 8.1.1 | Design loads..... | 18 |
| 8.1.2 | Minimum wall thickness..... | 18 |
| 8.1.3 | Minimum wall thickness against internal pressure..... | 18 |
| 8.1.4 | Minimum wall thickness against dynamic pressure alterations..... | 18 |
| 8.1.5 | Minimum wall thickness, $t_{\min DF}$, against running ductile fracture for gas phase pipelines..... | 19 |
| 8.1.6 | Minimum wall thickness, $t_{\min DF}$, against running ductile fracture for dense phase pipelines..... | 19 |
| 8.1.7 | Fracture toughness..... | 19 |
| 8.1.8 | Overview of the different aspects of wall thickness determination..... | 19 |
| 8.2 | Additional measures..... | 22 |
| 8.2.1 | Dynamic loads due to operation (alternating operation pressure)..... | 22 |
| 8.2.2 | Topographical profile..... | 22 |
| 8.2.3 | Fracture arrestors..... | 22 |
| 8.2.4 | Offshore pipelines..... | 22 |
| 9 | Construction..... | 22 |
| 9.1 | General..... | 22 |
| 9.2 | Pipeline pre-commissioning..... | 23 |
| 9.2.1 | Overview..... | 23 |
| 9.2.2 | Pipeline dewatering and drying..... | 23 |
| 9.2.3 | Preservation before pipeline commissioning..... | 23 |
| 10 | Operation..... | 23 |
| 10.1 | General..... | 23 |
| 10.2 | Pipeline commissioning..... | 23 |
| 10.2.1 | Initial filling and pressurization with product..... | 23 |
| 10.2.2 | Initial or baseline inspection..... | 24 |
| 10.3 | Pipeline shutdown..... | 24 |
| 10.4 | Pipeline system depressurization..... | 24 |
| 10.4.1 | General..... | 24 |
| 10.4.2 | Pipeline depressurization..... | 24 |
| 10.4.3 | Vent facilities..... | 25 |
| 10.5 | Inspection, monitoring and testing..... | 25 |
| 10.5.1 | General..... | 25 |
| 10.5.2 | In-line inspection procedure..... | 25 |
| 10.5.3 | Monitoring of water content and dew point..... | 26 |
| 10.5.4 | Network code or equivalent set of operational terms and conditions..... | 26 |
| 10.5.5 | Measurement of CO ₂ stream at each custody transfer point..... | 26 |
| 10.5.6 | Measurement of impurities..... | 26 |
| 10.5.7 | Action to be taken in the event of an exceedance of impurities..... | 27 |
| 10.5.8 | Measurement of CO ₂ mass flow rate..... | 27 |
| 11 | Re-qualification of existing pipelines for CO₂ service..... | 27 |
| | Annex A (informative) Examples of CO₂ stream compositions..... | 29 |
| | Annex B (informative) CO₂ characteristics..... | 33 |
| | Annex C (informative) Internal corrosion and erosion..... | 35 |

Annex D (informative) Avoidance of running ductile fracture: Approach for the evaluation of fracture arrest.....37

Annex E (informative) Data requirements for an integrity management plan.....39

Annex F (informative) Depressurization of a dense phase CO₂ stream avoiding low pipeline temperature issues40

Bibliography.....42