ISO 15875-2:2025-10 (E)

Plastics piping systems for hot and cold water installations - Crosslinked polyethylene (PE-X) - Part 2: Pipes

Contents

Page

Foreword v

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms,definitionsandsymbols 2
3.1 Terms and definitions 2
3.2 Symbols 4

4 Generic requirements, instructions and explanations 5
4.1 Designation PE-X 5
4.2 Application classes, design pressures and pipe dimension classes restrictions 5
4.3 Application classes -- Responsibility of the purchaser or specifier 5
4.4 Use of the parts of the ISO 15875 series 5
4.5 PE-X pipes provided with a thin barrier layer 5
4.6 Completeness of tests 5
4.7 Test result interchangeability restriction 5

5 Material 6
5.1 Pipe material 6
5.2 Evaluation of LPL-curves 6
5.3 Reference lines 7
5.4 Influence on water intended for human consumption 9
5.5 Barrier layer material 9
5.5.1 General 9
5.5.2 Thermal stability of the barrier layer material 9
5.5.3 Thermal stability of the adhesive layer material 9
5.5.4 Thermal stability of the outer layer material 9

6 General characteristics 10
6.1 Pipe construction 10
6.2 Appearance 10
6.3 Opacity 10
6.4 Oxygen permeability 10

7 Geometrical characteristics 10
7.1 Pipes without barrier layer(s) - General 10
7.2 Pipes without barrier layer - Dimensions of pipes 11
7.2.1 Outside diameters 11
7.2.2 Wall thicknesses and their tolerances 11
7.3 Pipes with barrier layer -- Dimensions of pipes 14
7.3.1 General 14
7.3.2 Option I - Dimensional integration of the barrier layer 14
7.3.3 Option II - Barrier layer on top 14

8 Mechanical characteristics 15

9 Physical and chemical characteristics 16

10 Performance requirements 17

11 Marking 17
11.1 General requirements 17
11.2 Minimum required marking 17

Annex A (normative) Pipe construction 18

Annex B (normative) Derivation of Scalc,max values 21

Annex C (normative)Proofofthethermalstabilityofthebarrierlayermaterialresp.adhesive layermaterialresp.outerlayermaterial--Testprocedure 23

Bibliography 26