

DIN EN 13407:2006-12 (E)

Wall-hung urinals - Functional requirements and test methods

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Principles of design	6
4.1	General	6
4.2	Flushing volume and flow rate	7
5	Classification	7
6	Functional requirements and test methods for class 1 products	8
6.1	Depth of water seal	8
6.2	Flushing requirements	8
6.2.1	Wash of bowl	8
6.2.2	Flushing of three plastics balls	8
6.2.3	Oversplashing	9
6.2.4	Discharge	9
6.3	Water absorption	9
6.4	Load resistance	9
6.5	Durability of class 1 products	9
6.6	Test methods	9
6.6.1	Testing the depth of water seal and flushing tests	9
6.6.2	Determination of water absorption	11
6.6.3	Static load test	12
7	Functional requirements and test methods for class 2 products	12
7.1	Depth of water seal	12
7.2	Cleanability	12
7.3	Load resistance	12
7.4	Durability of class 2 products	12
7.5	Test methods	13
7.5.1	Depth of water seal	13
7.5.2	Cleanability	13
8	Marking and product designation	13
9	Evaluation of conformity	14
9.1	General	14
9.2	Type testing	15
9.2.1	Initial type testing	15
9.2.2	Further type testing	15
9.2.3	Sample, testing and compliance criteria	15
9.3	Factory production control (FPC)	16
9.3.1	General	16
9.3.2	Testing equipment	16
9.3.3	Raw materials and components	16
9.3.4	Production testing and assessment	16
9.3.5	Non-conforming products	16

Annex A (normative) Test rig for urinals intended to be flushed by a flush valve	17
Annex B (normative) Test rig for urinals intended to be flushed by a manually operated flushing cistern	19
Annex C (normative) Test rig for urinals intended to be flushed by an automatic flushing cistern with valve-less outlet device	23
Annex ZA (informative) Clauses of this European Standard addressing the provisions of EU Construction Products Directive	25
Bibliography	29