DIN EN 14743:2006-01 (E)

Water conditioning equipment inside buildings - Softeners - Requirements for performance, safety and testing

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Requirements 8
4.1 Softener specification 8
4.2 Quality of materials and chemicals 8
4.2.1 Cation exchange resin 8
4.2.2 Regenerating salt 8
4.3 Design and manufacturing specifications 9
4.3.1 Resistance to hydrostatic pressure 9
4.3.2 Resistance to cyclic pressure 9
4.3.3 Minimum and maximum operating pressure 9
4.3.4 Resistance to temperature 9
4.3.5 Electrical safety 9
4.3.6 Salt tank 9
4.3.7 Continuity of supply during regeneration 9
4.3.8 Protection against backflow and infiltration of brine 9
4.3.9 Noise level 9
4.3.10 Air vent 10
4.3.11 End connections 10
4.3.12 Drain connections 10
4.4 Operating specifications 10
4.4.1 Initiation of regeneration 10
4.4.2 Brining efficiency 10
4.4.3 Regeneration water 10
4.4.4 Quality of treated water after regeneration 10
4.4.5 Continuous flow rate 10
4.4.6 Pressure drop 10
4.4.7 Exchange capacity 11
4.5 Installation specifications 11
4.5.1 Connection to mains water supply and existing pipe network 11
4.5.2 Drain 11
4.5.3 Electrical connection 11

5 Labelling 11
5.1 Identification of equipment 11
5.2 Safety labelling 11

6 Technical documentation 12

7 Test methods 12
7.1 Test conditions 12
7.1.1 Ambiant air 12
7.1.2 Water and salt 12
7.1.3 Test rig 13
7.1.4 Analysis 13

7.2 Cation exchange resin 13
7.3 Technical documentation 14
7.4 Manufacturing tests 14
7.4.1 Resistance to hydrostatic pressure 14
7.4.2 Resistance to cyclic pressure 14
7.4.3 Continuity of water supply 15
7.4.4 Protection against backflow 15
7.4.5 Air displacement 15
7.5 Operating characteristics 15
7.5.1 General 15
7.5.2 Nominal flow rate 15
7.5.3 Regenerations 16
7.5.4 Exchange capacity 17
7.5.5 Brine efficiency 17
7.5.6 Regeneration water 17
7.5.7 Quality of treated water after a regeneration 17