

DIN EN 14897:2006-09 (E)

Water conditioning equipment inside buildings - Devices using mercury low-pressure ultraviolet radiators - Requirements for performance, safety and testing

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Definitions	4
4 Requirements	7
4.1 General	7
4.2 Radiation chamber	7
4.3 Low-pressure mercury UV lamps	7
4.4 Electrical	7
4.4.1 General	7
4.4.2 UV disinfection devices	7
4.4.3 UV bactericidal treatment devices	8
4.5 Performance	8
4.6 Labelling	8
4.7 Manual	9
5 Testing	9
5.1 General	9
5.2 Test rig and installation	10
5.3 Biodosimetric measurements	10
5.4 Performance test procedure	11
5.4.1 UV disinfection devices	11
5.4.2 Processing of the data	13
5.4.3 UV bactericidal treatment devices	15
5.4.4 Processing of the data	15
Annex A (normative) Requirements for the device sensor	17
A.1 Calibration	17
A.2 Selectivity	17
A.3 Measuring range linearity	17
A.4 Measuring range and resolution	17
A.5 Temperature drift	18
A.6 Stability over time	18
Annex B (normative) Biodosimeter calibration	19
Annex C (informative) Monitoring window	22
Annex D (normative) Manufacturer's information for the type test	23
Annex E (normative) Manufacturer's information for the UV device user	25
Bibliography	26