

DIN EN 13476-3:2007-08 (E)

Plastics piping systems for non-pressure underground drainage and sewerage_ - Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE)_ - Part_3: Specifications for pipes and fittings with smooth internal and profiled external surface and the system, Type_B

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms, Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols	8
3.3 Abbreviations	9
4 Material	10
4.1 General	10
4.2 Unplasticized poly(vinyl chloride) (PVC-U)	10
4.2.1 General	10
4.2.2 Pipe and fitting material characteristics	10
4.2.3 Utilisation of non-virgin materials	11
4.3 Polypropylene (PP)	11
4.3.1 General	11
4.3.2 Pipe and fitting material characteristics	11
4.3.3 Melt mass-flow rate classification	12
4.3.4 Utilisation of non-virgin materials	12
4.4 Polyethylene (PE)	13
4.4.1 General	13
4.4.2 Material characteristics of pipes and injection-moulded fittings	13
4.4.3 Material characteristics of rotational-moulded fittings	13
4.4.4 Utilisation of non-virgin materials	14
4.4.5 Sealing ring retaining components	14
4.5 Sealing rings	14
4.6 Fused or welded joints	14
4.7 Adhesives for PVC-U	14
5 Designation of wall constructions and examples of typical jointing methods	15
5.1 Wall constructions designated as Type B	15
5.1.1 Ribbed or corrugated construction	15
5.1.2 Typical jointing methods for structured-wall type B	15
5.2 Designation and design of joints	16
6 Appearance and colour	16
7 Geometrical characteristics	17
7.1 General	17
7.2 Dimensions	17
7.2.1 Designation	17
7.2.2 Lengths of pipe	17
7.2.3 Diameters	17
7.2.4 Diameters and jointing dimensions of sockets and spigots	19
7.2.5 Wall thicknesses	20
7.3 Types of fittings	22
7.3.1 Design length of fittings	22
8 Physical characteristics	23
8.1 Unplasticized poly(vinyl chloride) (PVC-U)	23
8.1.1 Physical characteristics of PVC-U pipes	23

8.1.2	Physical characteristics of PVC-U fittings	23
8.2	Polypropylene (PP)	24
8.2.1	Physical characteristics of PP pipes	24
8.2.2	Physical characteristics of PP fittings	24
8.3	Polyethylene (PE)	24
8.3.1	Physical characteristics of PE pipes	24
8.3.2	Physical characteristics of PE fittings	25
9	Mechanical characteristics	25
9.1	Mechanical characteristics of pipes	25
9.1.1	General requirements	25
9.1.2	Ring flexibility	26
9.1.3	Tensile strength	27
9.2	Mechanical characteristics of fittings	27
10	Performance requirements	28
11	Marking	29
11.1	General	29
11.2	Minimum required marking	30
11.2.1	Pipes	30
11.2.2	Fittings	30
11.3	Additional marking	31
11.3.1	General	31
11.3.2	Third party certified pipes and fittings	31
Annex A (normative)	Virgin PVC-U material	32
Annex B (normative)	Utilisation of non-virgin PVC-U material	33
B.1	Reprocessible and recyclable material from pipes and fittings	33
B.2	External reprocessible and recyclable materials with agreed specification	33
B.3	External reprocessible and recyclable materials not covered by an agreed specification	33
Annex C (normative)	Virgin PP material	35
Annex D (normative)	Utilisation of non-virgin PP material	36
D.1	Reprocessible and recyclable material from pipes and fittings	36
D.2	External reprocessible and recyclable materials with an agreed specification	36
D.3	External reprocessible and recyclable materials not covered by an agreed specification	36
Annex E (normative)	Virgin PE material	37
Annex F (normative)	Utilisation of non-virgin PE material	38
F.1	Reprocessible and recyclable material from pipes and fittings	38
F.2	External reprocessible and recyclable materials with an agreed specification	38
F.3	External reprocessible and recyclable materials not covered by an agreed specification	38
F.4	External reprocessible and recyclable material from PE rotational-moulded fittings and other components	39
Annex G (normative)	Impact test at 23 °C	40
Annex H (normative)	Impact test at – 10 °C	41
Annex I (normative)	Ring flexibility test at 20 % diametric deflection	42
Annex J (informative)	Survey of possible use of reprocessible and recyclable material	43