

# DIN 630:2011-02 (E)

## Rolling bearings - Self aligning ball bearings - Double row with cylindrical or tapered bore

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>3</b>
<b>1 Scope</b> .....		<b>4</b>
<b>2 Normative references</b> .....		<b>4</b>
<b>3 Terms, definitions and symbols</b> .....		<b>4</b>
<b>4 Type, designation, dimensions</b> .....		<b>4</b>
<b>5 Material</b> .....		<b>10</b>
<b>6 Design</b> .....		<b>10</b>
<b>7 Mounting</b> .....		<b>10</b>
<b>Annex A (informative) Explanatory notes</b> .....		<b>11</b>
<b>Bibliography</b> .....		<b>12</b>
<b>Figures Figure 1 -- Cylindrical bore without seals</b> .....		<b>5</b>
<b>Figure 2 -- Tapered bore without seals</b> .....		<b>5</b>
<b>Figure 3 -- Cylindrical bore with two seals (2RS)</b> .....		<b>5</b>
<b>Figure 4 -- Tapered bore with two seals (2RS)</b> .....		<b>5</b>
<b>Tables Table 1 -- Dimensions and symbols for self-aligning ball bearings without seals</b> .....		<b>6</b>
<b>Table 2 -- Dimensions and symbols for self-aligning ball bearings with two seals</b> .....		<b>9</b>