

# ISO 2982-2:2013-04 (E)

## Rolling bearings - Accessories - Part 2: Dimensions for locknuts and locking devices

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols .....</b>	<b>1</b>
<b>4.1</b>	<b>General .....</b>	<b>1</b>
<b>4.2</b>	<b>Locknuts with 4 slots .....</b>	<b>2</b>
<b>4.3</b>	<b>Lockwashers with straight inner tab .....</b>	<b>3</b>
<b>4.4</b>	<b>Locknuts with 8 slots .....</b>	<b>4</b>
<b>4.5</b>	<b>Locking clip assemblies .....</b>	<b>5</b>
<b>5</b>	<b>Dimensions .....</b>	<b>5</b>
<b>5.1</b>	<b>Locknuts with 4 slots .....</b>	<b>5</b>
<b>5.2</b>	<b>Lockwashers with straight inner tab .....</b>	<b>7</b>
<b>5.3</b>	<b>Locknuts with 8 slots .....</b>	<b>8</b>
<b>5.4</b>	<b>Locking clip assemblies .....</b>	<b>9</b>
	<b>Annex A (informative) Lockwashers with bent inner tab .....</b>	<b>11</b>
	<b>Bibliography .....</b>	<b>13</b>