

# ISO 7902-2:2020 (E)

## Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings — Part 2: Functions used in the calculation procedure

---

### Contents

|     |  |
|-----|--|
|     | Foreword   |
| 1   | Scope  |
| 2   | Normative references   |
| 3   | Terms and definitions  |
| 4   | Tables of basic bearing characteristics  |
| 5   | Graphs of basic bearing characteristics  |
| 6   | Friction power loss  |
| 7   | Lubricant flow rate resulting from feed pressure   |
| 7.1 | General  |
| 7.2 | Lubrication hole located opposite to direction of load   |
| 7.3 | Lubrication hole located at 90° to direction of load   |
| 7.4 | Lubrication holes located at 90° to direction of load  |
| 7.5 | Circumferential groove (full groove)   |
| 7.6 | Circumferential groove (partial groove)  |
| 7.7 | Lubrication pocket, located opposite to direction of load  |
| 7.8 | Lubrication pocket located at 90° to direction of application load   |
| 7.9 | Two lubrication pockets at ±90° to direction of load   |
| 8   | Effective dynamic viscosity, $\eta_{\text{eff}}$ , of the lubricant as a function of effective bearing temperature, $T_{\text{eff}}$ |

Page count: 68