

# ISO 12131-2:2001-04 (E)

## Plain bearings - Hydrodynamic plain thrust pad bearings under steady-state conditions - Part 2: Functions for the calculation of thrust pad bearings

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | iv          |
| Introduction ..... |   | v           |
| 1                  | Scope .....   | 1           |
| 2                  | Normative reference .....   | 1           |
| 3                  | Functions for the thrust pad bearing .....  | 2           |
| 3.1                | Characteristic value of load carrying capacity * BF as a function of the relative bearing length B/L and the relative minimum lubricant film thickness $h_{min} / C_{wed}$ .....          | 2           |
| 3.2                | Characteristic value of friction for thrust pad bearings * Bf as a function of the relative bearing width B/L and the relative minimum lubricant film thickness $h_{min} / C_{wed}$ ..... | 4           |
| 3.3                | Relative lubricant flow rates * 1Q and * 3Q as a function of the relative bearing width B/L and the relative minimum lubricant film thickness $h_{min} / C_{wed}$ .....                   | 6           |
| 4                  | Effective dynamic viscosity of the lubricant $Deff$ as a function of the effective lubricant film temperature $T_{eff}$ .....   | 9           |
| Bibliography ..... |   | 11          |