

# ISO 12130-1:2001-11 (E)

## Plain bearings - Hydrodynamic plain tilting pad thrust bearings under steady-state conditions - Part 1: Calculation of tilting pad thrust bearings

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Fundamentals, assumptions and premises</b> .....	<b>2</b>
<b>4</b>	<b>Symbols, terms and units</b> .....	<b>3</b>
<b>5</b>	<b>Calculation procedure</b> .....	<b>6</b>
<b>5.1</b>	<b>Loading operations</b> .....	<b>6</b>
<b>5.2</b>	<b>Coordinate of centre of pressure</b> .....	<b>7</b>
<b>5.3</b>	<b>Load-carrying capacity</b> .....	<b>7</b>
<b>5.4</b>	<b>Frictional power</b> .....	<b>9</b>
<b>5.5</b>	<b>Lubricant flow rate</b> .....	<b>9</b>
<b>5.6</b>	<b>Heat balance</b> .....	<b>10</b>
<b>5.7</b>	<b>Minimum lubricant film thickness and specific bearing load</b> .....	<b>13</b>
<b>5.8</b>	<b>Operating conditions</b> .....	<b>13</b>
<b>5.9</b>	<b>Further influence factors</b> .....	<b>14</b>
<b>Annex A (normative) Examples of calculation</b> .....		<b>15</b>
<b>A.1</b>	<b>Example</b> .....	<b>15</b>
<b>A.2</b>	<b>Example</b> .....	<b>19</b>
<b>Bibliography</b> .....		<b>24</b>