

# ISO 12130-2:2001-11 (E)

## Plain bearings - Hydrodynamic plain tilting pad thrust bearings under steady-state conditions - Part 2: Functions for calculation of tilting pad thrust bearings

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative reference .....</b>	<b>1</b>
<b>3</b>	<b>Functions for the tilting-pad thrust bearing .....</b>	<b>2</b>
<b>3.1</b>	<b>General .....</b>	<b>2</b>
<b>3.2</b>	<b>Characteristic value of load-carrying capacity <math>F^*</math> as a function of the relative bearing width <math>B/L</math> and the relative minimum lubricant film thickness <math>h_{min}/C_{wed}</math> .....</b>	<b>2</b>
<b>3.3</b>	<b>Characteristic value of friction <math>f^*</math> as a function of the relative bearing width <math>B/L</math> and the relative minimum lubricant film thickness <math>h_{min}/C_{wed}</math> .....</b>	<b>4</b>
<b>3.4</b>	<b>Relative lubricant flow rates <math>^* 1Q</math> and <math>^* 3Q</math> as a function of the relative bearing width <math>B/L</math> and the relative minimum lubricant film thickness <math>h_{min}/C_{wed}</math> .....</b>	<b>5</b>
<b>3.5</b>	<b>Relative pressure centre coordinate or tilting-pad supporting point <math>^* Fa</math> as a function of the relative bearing width <math>B/L</math> and the relative minimum lubricant film thickness <math>h_{min}/C_{wed}</math> .....</b>	<b>8</b>
<b>4</b>	<b>Effective dynamic viscosity of the lubricant <math>\eta_{eff}</math> as a function of the effective lubricant film temperature <math>T_{eff}</math> .....</b>	<b>10</b>
Bibliography .....		12