

DIN EN 14398-2:2008-11 (E)

Cryogenic vessels - Large transportable non-vacuum insulated vessels - Part 2: Design, fabrication, inspection and testing (includes Amendment A2:2008)

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms, definitions and symbols | 7 |
| 3.1 | Terms and definitions | 7 |
| 3.2 | Symbols | 8 |
| 4 | Design | 9 |
| 4.1 | Design options | 9 |
| 4.1.1 | General | 9 |
| 4.1.2 | Design by calculation | 9 |
| 4.1.3 | Design by calculation and pressure strengthening | 9 |
| 4.1.4 | Design by calculation supplemented with experimental methods | 10 |
| 4.2 | Common design requirements | 10 |
| 4.2.1 | General | 10 |
| 4.2.2 | Design specification | 10 |
| 4.2.3 | Design loads | 11 |
| 4.2.4 | Fatigue | 13 |
| 4.2.5 | Corrosion allowance | 13 |
| 4.2.6 | Inspection openings | 13 |
| 4.2.7 | Pressure relief | 14 |
| 4.2.8 | Valves | 14 |
| 4.2.9 | Insulation | 14 |
| 4.2.10 | Degree of filling | 14 |
| 4.2.11 | Electrical continuity | 15 |
| 4.3 | Design by calculation | 15 |
| 4.3.1 | General | 15 |
| 4.3.2 | Vessel | 15 |
| 4.3.3 | Attachments | 16 |
| 4.3.4 | Piping and accessories | 16 |
| 4.3.5 | Calculation formulae | 17 |
| 4.3.6 | Calculations for operating loads | 25 |
| 5 | Fabrication | 53 |
| 5.1 | General | 53 |
| 5.2 | Cutting | 53 |
| 5.3 | Cold forming | 54 |
| 5.3.1 | Austenitic stainless steel | 54 |
| 5.3.2 | Ferritic steel | 54 |
| 5.4 | Hot forming | 55 |
| 5.4.1 | General | 55 |
| 5.4.2 | Austenitic stainless steel | 55 |
| 5.4.3 | Ferritic steel | 55 |
| 5.5 | Manufacturing tolerances | 55 |
| 5.5.1 | Plate alignment | 55 |
| 5.5.2 | Thickness | 57 |
| 5.5.3 | Dished ends | 57 |
| 5.5.4 | Cylinders | 57 |

| | | |
|--|---|----|
| 5.6 | Welding | 60 |
| 5.6.1 | General | 60 |
| 5.6.2 | Qualification | 60 |
| 5.6.3 | Temporary attachments | 60 |
| 5.6.4 | Welded joints | 60 |
| Non-welded joints | | 61 |
| 5.7 | 6 Inspection and testing | 61 |
| 6.1 | Quality plan | 61 |
| 6.1.1 | Inspection stages during manufacture of a vessel | 61 |
| 6.1.2 | Additional inspection stages during manufacture of a large transportable cryogenic vessel | 62 |
| 6.2 | Production control test plates | 62 |
| 6.2.1 | Requirements | 62 |
| 6.2.2 | Extent of testing | 62 |
| 6.3 | Non-destructive testing | 63 |
| 6.3.1 | General | 63 |
| 6.3.2 | Extent of examination for surface imperfections | 63 |
| 6.3.3 | Extent of examination for volumetric imperfections | 63 |
| 6.3.4 | Acceptance levels | 64 |
| 6.4 | Rectification | 65 |
| 6.5 | Pressure testing | 66 |
| Annex A (informative) Elastic stress analysis | | 67 |
| A.1 | General | 67 |
| A.2 | Terminology | 67 |
| A.2.1 | Stress intensity | 67 |
| A.2.2 | Gross structural discontinuity | 68 |
| A.2.3 | Local structural discontinuity | 68 |
| A.2.4 | Normal stress | 68 |
| A.2.5 | Shear stress | 68 |
| A.2.6 | Membrane stress | 68 |
| A.2.7 | Primary stress | 69 |
| A.2.8 | Primary local membrane stress | 69 |
| A.2.9 | Secondary stress | 69 |
| A.2.10 | Peak stress | 69 |
| A.3 | Limit for longitudinal compressive general membrane stress | 69 |
| A.4 | Stress categories and stress limits for general application | 70 |
| A.4.1 | General | 70 |
| A.4.2 | General primary membrane stress category | 70 |
| A.4.3 | Local primary membrane stress category | 70 |
| A.4.4 | General or local primary membrane plus primary bending stress category | 70 |
| A.4.5 | Primary plus secondary stress category | 70 |
| A.4.6 | Thermal stress | 70 |
| A.5 | Specific criteria, stress categories and stress limits for limited application | 71 |
| A.5.1 | General | 71 |
| A.5.2 | Attachments and supports | 71 |
| A.5.3 | Nozzles and openings | 71 |
| A.5.4 | Additional stress limits | 72 |
| Annex B (normative) Additional requirements for 9 % Ni steel | | 76 |
| B.1 | Introduction | 76 |
| B.2 | Specific requirements | 76 |
| Annex C (normative) Pressure strengthening of vessels from austenitic stainless steels | | 78 |
| C.1 | Introduction | 78 |
| C.2 | Scope | 78 |
| C.3 | Definitions and units of measurement | 78 |

| | | |
|---|--|-----------|
| C.4 | Materials | 79 |
| C.5 | Design | 80 |
| C.5.1 | General | 80 |
| C.5.2 | Design for internal pressure | 80 |
| C.6 | Manufacturing and inspection | 83 |
| C.6.1 | Strengthening procedure | 83 |
| C.6.2 | Procedure record | 83 |
| C.6.3 | Welding | 83 |
| C.6.4 | Pressure vessel drawing | 84 |
| C.6.5 | Data plate | 84 |
| C.7 | Comments | 84 |
| C.7.1 | Strengthening theory | 84 |
| C.7.2 | Work-hardened material | 86 |
| C.7.3 | Derivation of formulae | 86 |
| C.7.4 | Deformations at strengthening | 87 |
| Annex D (informative) Specific weld details | | 90 |
| D.1 | Field of application | 90 |
| D.2 | Weld detail | 90 |
| D.2.1 | Joggle joint | 90 |
| D.2.2 | Intermediate ends | 90 |
| D.2.3 | Backing strip | 91 |
| D.2.4 | End plate closure | 91 |
| D.2.5 | Non full penetration nozzle weld | 91 |
| D.2.6 | Non continuous fillet weld on attachments | 91 |
| D.3 | Oxygen service requirements | 91 |
| Annex E (normative) Increased material property for austenitic stainless steel | | 95 |
| Bibliography | | 96 |