ISO 21013-1:2008-06 (E)

Cryogenic vessels - Pressure-relief accessories for cryogenic service - Part 1: Reclosable pressure-relief valves

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Requirements 3
4.1 General 3
4.2 Design 3
4.2.1 Design temperature 3
4.2.2 Drainage 3
4.2.3 Stem guiding 3
4.2.4 Inserts 3
4.2.5 Sublimating fluids service 3
4.2.6 Electric continuity 3
4.2.7 Set pressure 3
4.2.8 Minimum shell thickness 3
4.3 Materials 4
4.3.1 General 4
4.3.2 Metallic materials 4
4.3.3 Non-metallic materials 4
4.3.4 Corrosion resistance 4
4.3.5 Gas material compability 5
4.3.6 Acetylene compatibility 5

5 Qualification and Testing 5
5.1 Type approval 5
5.1.1 Verification of the design 5
5.1.2 Model number 5
5.2 Type approval tests 5
5.2.1 Ambient condition tests 5
5.2.2 Cryogenic tests 6
5.2.3 Alternate cryogenic tests 7
5.3 Production testing 7

6 Determination of the certified coefficient of discharge (Kdr) 7

7 Set pressure tolerances 8

8 Re-seating pressure 8

9 Cleanliness 8

10 Marking 8
10.1 Marking on the body of the pressure-relief valve 8
10.2 Marking on an identification plate 8
11 Sealing 9

Bibliography 10