

DIN EN 14129:2014-05 (E)

LPG Equipment and accessories - Pressure relief valves for LPG pressure vessels

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Operating conditions	10
5	Materials	10
5.1	General	10
5.2	Metallic materials	10
5.3	Non-metallic components	11
5.4	Lubricants, sealants, and adhesives	11
5.5	Certification	11
6	Design	12
6.1	General	12
6.2	Design parameters	13
6.3	Threads	14
6.4	Springs	14
6.5	Additional requirements	14
6.6	Pressure relief valve with parallel thread	15
6.7	Pressure relief valve for use with a changeover manifold	15
6.8	Pilot operated pressure relief valve	15
7	Testing of the design	16
7.1	General	16
7.2	Test requirements	17
7.3	Dimensional checks	19
7.4	Hydraulic proof test	19
7.5	Overtorquing test	19
7.6	Start to discharge pressure test	19
7.7	Discharge capacity test	20
7.8	Leak tightness tests	20
7.9	Ageing test	20
7.10	Endurance test	21
7.11	Stress cracking test	21
7.11.1	General	21
7.11.2	Mercurous nitrate immersion test	21
7.11.3	Moist ammonia air stress cracking test	21
7.12	Vacuum test	21
7.13	Visual inspection	21
7.14	Test records	22
8	Marking	22
8.1	Pressure relief valves	22
8.2	Thermal expansion valves	22
8.3	Pilot operated pressure relief valve	23

9	Operating instructions	23
10	Packaging	24
	Annex A (informative) Terms used with LPG pressure relief valves	25
	Annex B (normative) Special low temperature requirements for valves	26
	Annex C (normative) Ageing test	27
C.1	General	27
C.2	Ultraviolet light	27
C.3	Rain	27
	Annex D (informative) Environment checklist	30
	Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC	31
	Bibliography	32