ISO 10462:2013-12 (E)

Gas cylinders - Acetylene cylinders - Periodic inspection and maintenance

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 General 3
4.1 Intervals between periodic inspections 3
4.2 Requirements for inspection 3

5 Preparation of the acetylene cylinder 3
5.1 Depressurization of the acetylene cylinder 3
5.2 Preparation for external visual inspection 4
5.3 Removal of the valve 4
5.4 Removal of neck/core hole filters 4

6 Inspection and maintenance 5
6.1 External visual inspection 5
6.2 Inspection of the porous material 5
6.3 Addition of non-monolithic porous material 6
6.4 Replacement of porous material 7
6.5 Inspection of fusible plugs 7
6.6 Inspection of valves 7
6.7 Inspection of cylinder neck 7
6.8 Reassembly 8

7 Cylindermarkingandidentification 8

8 Records 9

9 Rejection and rendering cylinders unserviceable 9

10 Disposal of unserviceable cylinders 9

Annex A (informative) Tops of acetylene cylinders containing monolithic porous material 11

Annex B (normative) External visual inspection 14

Annex C (normative) Determination of the top clearance 17

Annex D (normative) Cracks in the porous material 19

Annex E (informative) Rings for indicating the date of the next periodic inspection for gas cylinders 20

Bibliography 22