

ISO 11363-2:2017-10 (E)

Gas cylinders - 17E and 25E taper threads for connection of valves to gas cylinders - Part 2: Inspection gauges

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Requirements	2
4.1	Materials	2
4.2	Thread profile	2
4.3	Thread handedness	4
4.4	Taper	4
4.5	Pitch, P	4
5	Gauge dimensions	4
6	Inspection gauges	5
6.1	Gauges for cylinder neck thread	5
6.1.1	Single-part plug gauges	5
6.1.2	Two-part plug gauges, small end diameter	6
6.1.3	Two-part plug gauges, large end diameter	7
6.2	Gauges for valve stem thread	8
6.2.1	Single-part ring gauges	8
6.2.2	Two-part ring gauges, small end diameter	8
6.2.3	Two-part ring gauges, large end diameter	9
7	Check gauges	10
8	Use of inspection gauges	10
8.1	Plain gauges	10
8.2	Threaded plug gauges	10
8.3	Accept or reject criteria using plug gauges	10
8.4	Accept or reject criteria using ring gauges	11
9	Verification of inspection gauges	12
9.1	General	12
9.2	Plug gauges	13
9.3	Ring gauges	13
9.4	Use of check plug gauges	13
10	Identification	13
10.1	Inspection gauges	13
10.2	Check gauges	13
Annex A (informative)	Examples of calculation for thread gauge dimensions on the large end diameter	15
Annex B (informative)	Limitation of gauging system	17
Bibliography		19