ISO 11363-2:2017-10 (E)

Gas cylinders - 17E and 25E taper threads for connection of valves to gas cylinders - Part 2: Inspection gauges

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Requirements 2
4.1 Materials 2
4.2 Thread profile 2
4.3 Thread handedness 4
4.4 Taper 4
4.5 Pitch, P 4

5 Gauge dimensions 4

6 Inspection gauges 5
6.1 Gauges for cylinder neck thread 5
6.1.1 Single-part plug gauges 5
6.1.2 Two-part plug gauges, small end diameter 6
6.1.3 Two-part plug gauges, large end diameter 7
6.2 Gauges for valve stem thread 8
6.2.1 Single-part ring gauges 8
6.2.2 Two-part ring gauges, small end diameter 8
6.2.3 Two-part ring gauges, large end diameter 9

7 Check gauges 10

8 Use of inspection gauges 10
8.1 Plain gauges 10
8.2 Threaded plug gauges 10
8.3 Accept or reject criteria using plug gauges 10
8.4 Accept or reject criteria using ring gauges 11

9 Verificationofinspectiongauges 12
9.1 General 12
9.2 Plug gauges 13
9.3 Ring gauges 13
9.4 Use of check plug gauges 13

10 Identification 13
10.1 Inspection gauges 13
10.2 Check gauges 13

Annex A (informative) Examples of calculation for thread gauge dimensions on the large end diameter 15

Annex B (informative) Limitation of gauging system 17

Bibliography 19