

ISO 20421-1:2019 (E)

Cryogenic vessels — Large transportable vacuum-insulated vessels — Part 1: Design, fabrication, inspection and testing

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	General requirements
6	Mechanical loads
6.1	General
6.2	Load during the pressure test
7	Chemical effects
8	Thermal conditions
9	Materials
9.1	Selection of materials
9.2	Inspection documentation
10	Design
10.1	Design options
10.1.1	General
10.1.2	Design by calculation
10.1.3	Design by calculation and pressure strengthening
10.1.4	Design of components by calculation supplemented with experimental methods
10.2	Common design requirements
10.2.1	General
10.2.2	Design specification
10.2.3	Design loads
10.2.3.1	General
10.2.3.2	Inner vessel
10.2.3.3	Outer jacket
10.2.3.4	Self-supporting vessels
10.2.3.5	Inner-vessel supports
10.2.3.6	Surge plates
10.2.3.7	Outer-jacket supports
10.2.3.8	Fastening points
10.2.3.9	Protection of upper fittings
10.2.3.10	Stability
10.2.3.11	Piping and valves
10.2.4	Fatigue
10.2.5	Corrosion allowance
10.2.6	Inspection openings
10.2.7	Pressure relief
10.2.7.1	General
10.2.7.2	Inner vessel

- 10.2.7.3 Outer jacket
- 10.2.7.4 Piping
- 10.2.8 Valves
- 10.2.9 Insulation
- 10.2.10 Degree of filling
- 10.2.11 Electrical continuity
- 10.3 Design by calculation
- 10.3.1 General
- 10.3.2 Inner vessel
- 10.3.2.1 General
- 10.3.2.2 Design pressure, p
- 10.3.2.3 Material properties, K
- 10.3.2.3.1 General
- 10.3.2.3.2 K20
- 10.3.2.3.3 Kt
- 10.3.2.3.4 Brittleness
- 10.3.2.3.5 Elongation
- 10.3.2.4 Safety factors S, Sp and Sk
- 10.3.2.5 Weld joint factor, η
- 10.3.2.6 Corrosion allowances, c
- 10.3.3 Outer jacket
- 10.3.3.1 General
- 10.3.3.2 Calculation pressure, p
- 10.3.3.3 K20
- 10.3.3.4 Safety factors S, Sp and Sk in relation to K, K20 or KT
- 10.3.3.5 Plastic deformation
- 10.3.3.6 Weld joint factor, η
- 10.3.3.7 Corrosion allowances, c
- 10.3.4 Attachments
- 10.3.5 Piping and accessories
- 10.3.6 Calculation formula
- 10.3.6.1 Cylindrical shells and spheres subject to internal pressure (pressure on the concave surface)
 - 10.3.6.1.1 Field of application
 - 10.3.6.1.2 Openings
 - 10.3.6.1.3 Calculation
- 10.3.6.2 Cylindrical shells subject to external pressure (pressure on the convex surface)
 - 10.3.6.2.1 Field of application
 - 10.3.6.2.2 Openings
 - 10.3.6.2.3 Calculation
- 10.3.6.3 Spheres subject to external pressure (pressure on the convex surface)
- 10.3.6.4 Dished ends
 - 10.3.6.4.1 Field of application
 - 10.3.6.4.2 Straight flange
 - 10.3.6.4.3 Internal-pressure calculation (pressure on concave surface)
- 10.3.6.5 Cones subject to internal or external pressure
 - 10.3.6.5.1 Field of application
 - 10.3.6.5.2 Openings
 - 10.3.6.5.3 Non-destructive testing
 - 10.3.6.5.4 Corner area
 - 10.3.6.5.5 Internal-pressure calculation (pressure on concave surface) $|\varphi| \leq 70^\circ$
 - 10.3.6.5.6 Internal-pressure calculation (pressure on the concave surface) $|\varphi| > 70^\circ$
 - 10.3.6.5.7 External-pressure calculation (pressure on the convex surface)
- 10.3.6.6 Flat ends
 - 10.3.6.6.1 Symbols and units
 - 10.3.6.6.2 Field of application
 - 10.3.6.6.3 Openings
 - 10.3.6.6.4 Calculation
- 10.3.6.7 Openings in cylinders, spheres and cones
 - 10.3.6.7.1 Field of application
 - 10.3.6.7.2 Reinforcement methods
 - 10.3.6.7.3 Design of openings
 - 10.3.6.7.4 Calculation
- 10.3.7 Calculations for operating loads

- 11 Fabrication**
 - 11.1 General
 - 11.2 Cutting
 - 11.3 Cold forming
 - 11.3.1 Austenitic stainless steel
 - 11.3.2 Ferritic steel
 - 11.3.3 Aluminium or aluminium alloy
 - 11.4 Hot forming
 - 11.4.1 General
 - 11.4.2 Austenitic stainless steel
 - 11.4.3 Ferritic steel
 - 11.4.4 Aluminium or aluminium alloy
 - 11.5 Manufacturing tolerances
 - 11.5.1 General
 - 11.5.2 Plate alignment
 - 11.5.3 Thickness
 - 11.5.4 Dished ends
 - 11.5.5 Cylinders
 - 11.6 Welding
 - 11.6.1 General
 - 11.6.2 Qualification
 - 11.6.3 Temporary attachments
 - 11.6.4 Welded joints
 - 11.7 Non-welded joints
- 12 Inspection and testing**
 - 12.1 Quality plan
 - 12.1.1 General
 - 12.1.2 Inspection stages during manufacture of an inner vessel
 - 12.1.3 Additional inspection stages during manufacture of a large transportable cryogenic vessel
 - 12.2 Production control test plates
 - 12.2.1 Requirements
 - 12.2.2 Extent of testing
 - 12.3 Non-destructive testing
 - 12.3.1 General
 - 12.3.2 Extent of examination for surface imperfections
 - 12.3.3 Extent of examination for inner-vessel weld seams
 - 12.3.4 Acceptance criteria for surface and volumetric imperfections as classified in ISO 6520-1
 - 12.3.4.1 Acceptance levels for predominantly static loaded vessels
 - 12.3.4.2 Acceptance criteria for fatigue loaded vessels
 - 12.3.4.3 Extent of examination of non-welded joints
 - 12.4 Rectification
 - 12.5 Pressure testing
- 13 Marking and labelling**
- 14 Final acceptance test**
- 15 Periodic inspection**
- 16 Documentation**
- Annex A (informative) Examples of tank plates**
 - A.1 Example 1: Tank plate (of the complete tank) for fixed tanks of road tankers (tank vehicles), demountable tanks, tank containers and tank swap bodies
 - A.2 Example 2 :Tank plate for the inner vessel of fixed tanks of road tankers (tank vehicles), demountable tanks, tank containers and tank swap bodies
- Annex B (informative) Elastic stress analysis**
 - B.1 General
 - B.2 Terminology

- B.2.1 Stress intensity
- B.2.2 Gross structural discontinuity
- B.2.3 Local structural discontinuity
- B.2.4 Normal stress
- B.2.5 Shear stress
- B.2.6 Membrane stress
- B.2.7 Primary stress
- B.2.8 Primary local membrane stress
- B.2.9 Secondary stress
- B.2.9.1 Peak stress
- B.3 Limit for longitudinal compressive general membrane stress
- B.4 Stress categories and stress limits for general application
- B.4.1 General
- B.4.2 General primary membrane stress category
- B.4.3 Local primary membrane stress category
- B.4.4 General or local primary membrane plus primary bending stress category
- B.4.5 Primary plus secondary stress category
- B.4.6 Thermal stress
- B.5 Specific criteria, stress categories and stress limits for limited application
- B.5.1 General
- B.5.2 Attachments and supports
- B.5.3 Nozzles and openings
- B.5.4 Additional stress limits

Annex C (normative) Additional requirements for 9 % Ni steel

- C.1 General
- C.2 Specific requirements

Annex D (normative) Pressure strengthening of vessels from austenitic stainless steels

- D.1 General
- D.2 Application of this annex
- D.3 Materials
- D.4 Design
- D.4.1 General
- D.4.2 Design for internal pressure
- D.4.2.1 Design stress values
- D.4.2.2 Calculation of the strengthening pressure
- D.4.2.3 Calculation of wall thicknesses
- D.4.3 Design for external pressure
- D.5 Manufacturing and inspection
- D.5.1 Strengthening procedure
- D.5.2 Procedure record
- D.5.3 Welding
- D.5.4 Pressure-vessel drawing
- D.5.5 Inspection and testing
- D.5.6 Data plate
- D.6 Comments
- D.6.1 Strengthening theory
- D.6.2 Work-hardened material
- D.6.3 Derivation of formula
- D.6.4 Deformations at strengthening

Annex E (informative) Specific weld details

- E.1 Field of application
- E.2 Weld detail
- E.2.1 Joggle joint
- E.2.2 Intermediate ends
- E.2.3 Backing strip
- E.2.4 End plate closure
- E.2.5 Nozzle weld
- E.2.6 Non-continuous fillet weld on attachments
- E.3 Oxygen service requirements

Annex F (normative) Outer-jacket relief devices

F.1	Field of application
F.2	Requirements
F.2.1	General
F.2.2	Design
F.2.3	Materials
F.2.4	Testing
F.2.5	Inspection
F.2.6	Marking

Annex G (informative) Base materials

Annex H (informative) Components subject to external pressure (pressure on the convex surface) — Calculation

H.1	General
H.2	Method 1
H.2.1	Cylindrical shells
H.2.1.1	Elastic buckling
H.2.1.2	Plastic deformation
H.2.1.3	Stiffening rings
H.2.2	Dished ends and spherical shells
H.2.2.1	Elastic buckling
H.3	Method 2
H.3.1	Cylindrical shells
H.3.1.1	Elastic buckling
H.3.1.2	Stiffening rings
H.3.2	Dished ends and spherical shells

Annex I (informative) Design of openings in cylinders, spheres and cones — Calculation

I.1	General
I.2	Method 1
I.3	Method 2
I.4	Reinforcement by increased nozzle thickness
I.4.1	General
I.4.2	Reinforcement by a combination of increased shell and nozzle thicknesses
I.4.3	Multiple openings

Annex J (normative) Reference material & equivalent thickness

J.1	General
J.2	Method A
J.2.1	Example 1
J.2.2	Example 2
J.3	Method B: Equivalent thickness

Annex K (normative) Refrigerated liquefied gases