ISO 11515:2022-08 (E)

Gas cylinders - Refillable composite reinforced tubes of water capacity between 450 l and 3000 l - Design, construction and testing

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols 5

5 Inspection and testing 6

6 Materials 6
6.1 Liner materials 6
6.2 Composite overwrap 7

7 Design and manufacture 7
7.1 General 7
7.2 Design submission 8
7.3 Manufacturing 9

8 Type approval procedure 10
8.1 General 10
8.2 Prototype tests 10
8.3 New design 11
8.4 Design variants 12
8.5 Type approval test procedures and criteria 17
8.5.1 General 17
8.5.2 Hydraulic proof pressure test 17
8.5.3 Hydraulic volumetric expansion test 17
8.5.4 Liner burst test 18
8.5.5 Tube burst test 18
8.5.6 Ambient cycle test 19
8.5.7 Environmental cycle test 20
8.5.8 Flaw test 21
8.5.9 Blunt impact test 23
8.5.10 Fire resistance test 24
8.5.11 Neck strength test 26
8.5.12 Leak test 27
8.5.13 Accelerated stress rupture test 27
8.5.14 Permeability test 28
8.5.15 Gas cycle test 28
8.5.16 Coatings test 29
8.5.17 Salt spray test 30
8.5.18 Acid environment test 30
8.5.19 Vacuum test 31
8.5.20 High velocity impact (gunfire) test 31
8.5.21 Glass transition temperature test 32
8.5.22 Resin shear strength test 32

8.6 Failure of type approval tests 32

9 Inspection and testing at time of manufacture 32
9.1 Liners for Type 2 and Type 3 tubes 32
9.2 Failure of load-sharing liner batch tests 33
9.3 Liners for Type 4 tubes 33
9.4 Failure of non-load sharing liner batch tests 34
9.5 Overwrap materials 34
9.6 Composite tube 35
9.7 Failure of batch tests 35

10 Tube marking 36
10.1 General 36
10.2 Additional marking 36

Annex A (informative) Example of a design approval certificate 37

Annex B (informative) Example of a test report 38

Annex C (normative) Ultrasonic inspection for seamless steel liners and metal tubing 40

Annex D (informative) Guidance for calculating permeation rates when using trace gases 44

Bibliography 45