

DIN EN 17533:2025-07 (E)

Gaseous hydrogen - Cylinders and tubes for stationary storage

| Contents | Page |
|--|-------------|
| European foreword | 7 |
| Introduction | 8 |
| 1 Scope..... | 9 |
| 2 Normative references..... | 9 |
| 3 Terms, definitions and symbols | 10 |
| 3.1 Terms and definitions..... | 10 |
| 3.2 Symbols | 15 |
| 4 Specified service conditions | 16 |
| 4.1 Maximum allowable working pressure | 16 |
| 4.2 Maximum allowable energy..... | 16 |
| 4.3 Maximum and minimum allowable temperature | 16 |
| 4.4 Pressure cycle life..... | 16 |
| 4.5 Methods to define the acceptable number of pressure cycles or fatigue behaviour for in service performance..... | 16 |
| 4.5.1 General..... | 16 |
| 4.5.2 Method 1 - Pressure cycling calculation using design standards for transportable applications - Method described in Annex A..... | 16 |
| 4.5.3 Method 2 - Fatigue evaluation using fracture mechanics - Method described in Annex B (Type 1 and Type 2) | 16 |
| 4.5.4 Method 3 - Fatigue evaluation based on performance testing - Method described in Annex C..... | 17 |
| 4.6 Service life | 17 |
| 5 Additional service conditions..... | 17 |
| 5.1 General..... | 17 |
| 5.2 Environmental conditions..... | 17 |
| 5.3 Fire conditions..... | 17 |
| 6 Information to be recorded..... | 17 |
| 6.1 General..... | 17 |
| 6.2 Statement of service..... | 17 |
| 6.3 Design, drawings and information | 18 |
| 6.4 Material property data..... | 19 |
| 6.5 Manufacturing data..... | 19 |
| 6.6 Retention of records | 19 |
| 7 Material properties | 20 |
| 7.1 Compatibility..... | 20 |
| 7.2 Steel..... | 20 |
| 7.3 Stainless steels..... | 20 |
| 7.4 Aluminium alloys..... | 20 |
| 7.5 Fibre material | 20 |
| 7.6 Matrix materials..... | 20 |
| 7.7 Plastic liner material | 20 |
| 8 Requirements for new design | 21 |

| | | |
|---------|---|----|
| 9 | Minimum requirement for new designs..... | 21 |
| 9.1 | Stress analysis..... | 21 |
| 9.1.1 | General | 21 |
| 9.1.2 | Burst pressure and fibre stress ratio (not applicable if Annex B is used) | 22 |
| 9.1.3 | Test pressure..... | 22 |
| 9.1.4 | Maximum defect size in metallic materials..... | 23 |
| 9.1.5 | Protection liner and boss against corrosion..... | 23 |
| 9.1.6 | Resistance to UV emissions..... | 23 |
| 9.1.7 | Resistance to humidity | 23 |
| 9.1.8 | Protective layer | 23 |
| 9.2 | Construction and workmanship..... | 23 |
| 9.2.1 | Materials | 23 |
| 9.2.2 | Openings, neck threads, neck ring, foot ring, attachment for support | 24 |
| 9.2.3 | Forming..... | 24 |
| 9.2.4 | Fibre winding..... | 24 |
| 9.2.5 | Curing of thermosetting resins..... | 25 |
| 9.2.6 | Autofrettage..... | 25 |
| 9.2.7 | Exterior environmental protection..... | 25 |
| 9.3 | Production and batch tests | 26 |
| 9.3.1 | Production tests | 26 |
| 9.3.2 | Batch tests | 26 |
| 10 | Markings..... | 29 |
| 11 | Preparation for dispatch..... | 30 |
| Annex A | (informative) Pressure cycling calculation using design standards for transportable applications | 31 |
| A.1 | General | 31 |
| A.2 | Requirements..... | 33 |
| A.2.1 | General requirements..... | 33 |
| A.2.2 | Specific requirements..... | 33 |
| A.3 | Marking | 35 |
| A.4 | Certificate | 36 |
| A.5 | Examples of calculation for PS (MAWP) | 36 |
| A.5.1 | Type 1 cylinder to EN ISO 9809-1 with P_w/P_h of 200/300 bar in Europe | 36 |
| A.5.2 | Type 3 cylinder to ISO 11119-2 with P_w/P_h of 200/300 bar in Europe | 36 |
| A.5.3 | Type 1 cylinder to EN ISO 9809-1 with P_w/P_h of 700/1 050 bar in Europe | 36 |
| A.5.4 | Type 3 cylinder to ISO 11119-2 with P_w/P_h of 1 000/1 500 bar in Europe..... | 36 |
| A.6 | Example of cycle life calculation | 37 |
| Annex B | (normative) Design and calculation and cycle life definition by fracture mechanics (Type 1 and Type 2)..... | 38 |
| B.1 | Purpose and scope | 38 |
| B.2 | Methodology..... | 38 |
| B.3 | Exemption for low alloy steels..... | 38 |

| | |
|---|-----------|
| Annex C (normative) Design evaluation based on performance testing | 39 |
| C.1 Testing | 39 |
| C.1.1 General..... | 39 |
| C.1.2 Material tests..... | 39 |
| C.1.3 Pressure vessel tests..... | 40 |
| C.1.4 Qualification and design changes | 43 |
| Annex D (normative) Test methods and acceptance criteria | 46 |
| D.1 Hydrogen compatibility..... | 46 |
| D.2 Hydrogen sensitivity tests for metals..... | 46 |
| D.2.1 General..... | 46 |
| D.2.2 Test method 1 - Fatigue testing of tensile specimens | 46 |
| D.2.3 Test method 2 - Fatigue testing of disks | 48 |
| D.3 Tensile properties of plastics | 49 |
| D.4 Softening temperature of plastics..... | 49 |
| D.5 Resin properties tests | 49 |
| D.6 Hydrostatic burst pressure test..... | 49 |
| D.7 Ambient temperature pressure cycling for cycle life definition..... | 50 |
| D.7.1 Full amplitude pressure cycling..... | 50 |
| D.7.2 Partial amplitude pressure cycling | 50 |
| D.7.3 Alternative to D.7.1 and D.7.2..... | 50 |
| D.7.4 Parameters to be monitored and recorded..... | 51 |
| D.8 Leak before break (LBB) test..... | 51 |
| D.9 Bonfire test..... | 51 |
| D.10 High strain impact test..... | 51 |
| D.11 Accelerated stress rupture test | 51 |
| D.12 Extreme temperature pressure cycling..... | 51 |
| D.13 Permeation test | 52 |
| D.14 Boss torque test..... | 52 |
| D.15 Hydrogen gas cycling test (for Type 4 only)..... | 52 |
| D.16 Hardness test..... | 53 |
| D.17 Hydraulic test..... | 53 |
| D.18 Leak test | 53 |
| D.19 Coating tests..... | 53 |
| D.20 Coating batch tests..... | 54 |
| D.20.1 Coating thickness..... | 54 |
| D.20.2 Coating adhesion..... | 54 |

| | | |
|----------------|--|-----------|
| D.21 | Impact damage test (optional) | 54 |
| Annex E | (informative) Verification of stress ratios using strain gauges | 55 |
| Annex F | (informative) Non-destructive examination (NDE) defect size by flawed pressure vessel cycling | 56 |
| Annex G | (informative) Manufacturer’s information for handling, use and inspection of pressure vessels | 57 |
| G.1 | General | 57 |
| G.2 | Distribution | 57 |
| G.3 | Reference to existing codes, standards and regulations | 57 |
| G.4 | Pressure vessel handling | 57 |
| G.5 | Installation | 57 |
| G.6 | Use of pressure vessels | 58 |
| G.7 | In-service inspection | 58 |
| G.7.1 | General | 58 |
| G.7.2 | Periodic re-qualification | 58 |
| G.7.3 | Pressure vessels having experienced impact damage | 58 |
| G.7.4 | Pressure vessels involved in fires | 58 |
| Annex H | (informative) Optional bonfire test | 59 |
| H.1 | General | 59 |
| H.2 | Cylinder test | 59 |
| H.2.1 | Cylinder set-up | 59 |
| H.2.2 | Fire source | 59 |
| H.2.3 | Temperature and pressure measurements | 59 |
| H.2.4 | General test requirements | 60 |
| H.2.5 | Test options | 60 |
| H.3 | PRD test | 60 |
| H.4 | Vent test | 61 |
| H.5 | System assessment | 61 |
| H.5.1 | Qualification limit envelope | 61 |
| H.5.2 | Service limit envelope | 61 |
| H.5.3 | Acceptable results | 61 |
| H.6 | Generation of a safety envelope and actual cylinder/PRD performance | 61 |
| Annex I | (informative) Information of factor of safety | 63 |
| I.1 | Purpose | 63 |
| I.2 | Background | 63 |
| I.3 | Recommended safety factor | 63 |
| I.4 | Discussion | 63 |

| | | |
|------------|-----------------------------|-----------|
| I.5 | Conclusions | 65 |
| I.6 | Recommendations..... | 65 |
| I.7 | Further reading..... | 65 |
| | Bibliography | 66 |