

# DIN EN 17533:2025-07 (E)

## Gaseous hydrogen - Cylinders and tubes for stationary storage

---

<b>Contents</b>	<b>Page</b>
European foreword .....	7
Introduction .....	8
1 Scope.....	9
2 Normative references.....	9
3 Terms, definitions and symbols .....	10
3.1 Terms and definitions.....	10
3.2 Symbols .....	15
4 Specified service conditions .....	16
4.1 Maximum allowable working pressure .....	16
4.2 Maximum allowable energy.....	16
4.3 Maximum and minimum allowable temperature .....	16
4.4 Pressure cycle life.....	16
4.5 Methods to define the acceptable number of pressure cycles or fatigue behaviour for in service performance.....	16
4.5.1 General.....	16
4.5.2 Method 1 - Pressure cycling calculation using design standards for transportable applications - Method described in Annex A.....	16
4.5.3 Method 2 - Fatigue evaluation using fracture mechanics - Method described in Annex B (Type 1 and Type 2) .....	16
4.5.4 Method 3 - Fatigue evaluation based on performance testing - Method described in Annex C.....	17
4.6 Service life .....	17
5 Additional service conditions.....	17
5.1 General.....	17
5.2 Environmental conditions.....	17
5.3 Fire conditions.....	17
6 Information to be recorded.....	17
6.1 General.....	17
6.2 Statement of service.....	17
6.3 Design, drawings and information .....	18
6.4 Material property data.....	19
6.5 Manufacturing data.....	19
6.6 Retention of records .....	19
7 Material properties .....	20
7.1 Compatibility.....	20
7.2 Steel.....	20
7.3 Stainless steels.....	20
7.4 Aluminium alloys.....	20
7.5 Fibre material .....	20
7.6 Matrix materials.....	20
7.7 Plastic liner material .....	20
8 Requirements for new design .....	21

<b>9</b>	<b>Minimum requirement for new designs</b> .....	<b>21</b>
<b>9.1</b>	<b>Stress analysis</b> .....	<b>21</b>
<b>9.1.1</b>	<b>General</b> .....	<b>21</b>
<b>9.1.2</b>	<b>Burst pressure and fibre stress ratio (not applicable if Annex B is used)</b> .....	<b>22</b>
<b>9.1.3</b>	<b>Test pressure</b> .....	<b>22</b>
<b>9.1.4</b>	<b>Maximum defect size in metallic materials</b> .....	<b>23</b>
<b>9.1.5</b>	<b>Protection liner and boss against corrosion</b> .....	<b>23</b>
<b>9.1.6</b>	<b>Resistance to UV emissions</b> .....	<b>23</b>
<b>9.1.7</b>	<b>Resistance to humidity</b> .....	<b>23</b>
<b>9.1.8</b>	<b>Protective layer</b> .....	<b>23</b>
<b>9.2</b>	<b>Construction and workmanship</b> .....	<b>23</b>
<b>9.2.1</b>	<b>Materials</b> .....	<b>23</b>
<b>9.2.2</b>	<b>Openings, neck threads, neck ring, foot ring, attachment for support</b> .....	<b>24</b>
<b>9.2.3</b>	<b>Forming</b> .....	<b>24</b>
<b>9.2.4</b>	<b>Fibre winding</b> .....	<b>24</b>
<b>9.2.5</b>	<b>Curing of thermosetting resins</b> .....	<b>25</b>
<b>9.2.6</b>	<b>Autofrettage</b> .....	<b>25</b>
<b>9.2.7</b>	<b>Exterior environmental protection</b> .....	<b>25</b>
<b>9.3</b>	<b>Production and batch tests</b> .....	<b>26</b>
<b>9.3.1</b>	<b>Production tests</b> .....	<b>26</b>
<b>9.3.2</b>	<b>Batch tests</b> .....	<b>26</b>
<b>10</b>	<b>Markings</b> .....	<b>29</b>
<b>11</b>	<b>Preparation for dispatch</b> .....	<b>30</b>
<b>Annex A</b>	<b>(informative) Pressure cycling calculation using design standards for transportable applications</b> .....	<b>31</b>
<b>A.1</b>	<b>General</b> .....	<b>31</b>
<b>A.2</b>	<b>Requirements</b> .....	<b>33</b>
<b>A.2.1</b>	<b>General requirements</b> .....	<b>33</b>
<b>A.2.2</b>	<b>Specific requirements</b> .....	<b>33</b>
<b>A.3</b>	<b>Marking</b> .....	<b>35</b>
<b>A.4</b>	<b>Certificate</b> .....	<b>36</b>
<b>A.5</b>	<b>Examples of calculation for PS (MAWP)</b> .....	<b>36</b>
<b>A.5.1</b>	<b>Type 1 cylinder to EN ISO 9809-1 with <math>P_w/P_h</math> of 200/300 bar in Europe</b> .....	<b>36</b>
<b>A.5.2</b>	<b>Type 3 cylinder to ISO 11119-2 with <math>P_w/P_h</math> of 200/300 bar in Europe</b> .....	<b>36</b>
<b>A.5.3</b>	<b>Type 1 cylinder to EN ISO 9809-1 with <math>P_w/P_h</math> of 700/1 050 bar in Europe</b> .....	<b>36</b>
<b>A.5.4</b>	<b>Type 3 cylinder to ISO 11119-2 with <math>P_w/P_h</math> of 1 000/1 500 bar in Europe</b> .....	<b>36</b>
<b>A.6</b>	<b>Example of cycle life calculation</b> .....	<b>37</b>
<b>Annex B</b>	<b>(normative) Design and calculation and cycle life definition by fracture mechanics (Type 1 and Type 2)</b> .....	<b>38</b>
<b>B.1</b>	<b>Purpose and scope</b> .....	<b>38</b>
<b>B.2</b>	<b>Methodology</b> .....	<b>38</b>
<b>B.3</b>	<b>Exemption for low alloy steels</b> .....	<b>38</b>

<b>Annex C (normative) Design evaluation based on performance testing</b> .....	<b>39</b>
<b>C.1 Testing</b> .....	<b>39</b>
<b>C.1.1 General</b> .....	<b>39</b>
<b>C.1.2 Material tests</b> .....	<b>39</b>
<b>C.1.3 Pressure vessel tests</b> .....	<b>40</b>
<b>C.1.4 Qualification and design changes</b> .....	<b>43</b>
<b>Annex D (normative) Test methods and acceptance criteria</b> .....	<b>46</b>
<b>D.1 Hydrogen compatibility</b> .....	<b>46</b>
<b>D.2 Hydrogen sensitivity tests for metals</b> .....	<b>46</b>
<b>D.2.1 General</b> .....	<b>46</b>
<b>D.2.2 Test method 1 – Fatigue testing of tensile specimens</b> .....	<b>46</b>
<b>D.2.3 Test method 2 – Fatigue testing of disks</b> .....	<b>48</b>
<b>D.3 Tensile properties of plastics</b> .....	<b>49</b>
<b>D.4 Softening temperature of plastics</b> .....	<b>49</b>
<b>D.5 Resin properties tests</b> .....	<b>49</b>
<b>D.6 Hydrostatic burst pressure test</b> .....	<b>49</b>
<b>D.7 Ambient temperature pressure cycling for cycle life definition</b> .....	<b>50</b>
<b>D.7.1 Full amplitude pressure cycling</b> .....	<b>50</b>
<b>D.7.2 Partial amplitude pressure cycling</b> .....	<b>50</b>
<b>D.7.3 Alternative to D.7.1 and D.7.2</b> .....	<b>50</b>
<b>D.7.4 Parameters to be monitored and recorded</b> .....	<b>51</b>
<b>D.8 Leak before break (LBB) test</b> .....	<b>51</b>
<b>D.9 Bonfire test</b> .....	<b>51</b>
<b>D.10 High strain impact test</b> .....	<b>51</b>
<b>D.11 Accelerated stress rupture test</b> .....	<b>51</b>
<b>D.12 Extreme temperature pressure cycling</b> .....	<b>51</b>
<b>D.13 Permeation test</b> .....	<b>52</b>
<b>D.14 Boss torque test</b> .....	<b>52</b>
<b>D.15 Hydrogen gas cycling test (for Type 4 only)</b> .....	<b>52</b>
<b>D.16 Hardness test</b> .....	<b>53</b>
<b>D.17 Hydraulic test</b> .....	<b>53</b>
<b>D.18 Leak test</b> .....	<b>53</b>
<b>D.19 Coating tests</b> .....	<b>53</b>
<b>D.20 Coating batch tests</b> .....	<b>54</b>
<b>D.20.1 Coating thickness</b> .....	<b>54</b>
<b>D.20.2 Coating adhesion</b> .....	<b>54</b>

<b>D.21</b>	<b>Impact damage test (optional)</b> .....	<b>54</b>
<b>Annex E</b>	<b>(informative) Verification of stress ratios using strain gauges</b> .....	<b>55</b>
<b>Annex F</b>	<b>(informative) Non-destructive examination (NDE) defect size by flawed pressure vessel cycling</b> .....	<b>56</b>
<b>Annex G</b>	<b>(informative) Manufacturer’s information for handling, use and inspection of pressure vessels</b> .....	<b>57</b>
<b>G.1</b>	<b>General</b> .....	<b>57</b>
<b>G.2</b>	<b>Distribution</b> .....	<b>57</b>
<b>G.3</b>	<b>Reference to existing codes, standards and regulations</b> .....	<b>57</b>
<b>G.4</b>	<b>Pressure vessel handling</b> .....	<b>57</b>
<b>G.5</b>	<b>Installation</b> .....	<b>57</b>
<b>G.6</b>	<b>Use of pressure vessels</b> .....	<b>58</b>
<b>G.7</b>	<b>In-service inspection</b> .....	<b>58</b>
<b>G.7.1</b>	<b>General</b> .....	<b>58</b>
<b>G.7.2</b>	<b>Periodic re-qualification</b> .....	<b>58</b>
<b>G.7.3</b>	<b>Pressure vessels having experienced impact damage</b> .....	<b>58</b>
<b>G.7.4</b>	<b>Pressure vessels involved in fires</b> .....	<b>58</b>
<b>Annex H</b>	<b>(informative) Optional bonfire test</b> .....	<b>59</b>
<b>H.1</b>	<b>General</b> .....	<b>59</b>
<b>H.2</b>	<b>Cylinder test</b> .....	<b>59</b>
<b>H.2.1</b>	<b>Cylinder set-up</b> .....	<b>59</b>
<b>H.2.2</b>	<b>Fire source</b> .....	<b>59</b>
<b>H.2.3</b>	<b>Temperature and pressure measurements</b> .....	<b>59</b>
<b>H.2.4</b>	<b>General test requirements</b> .....	<b>60</b>
<b>H.2.5</b>	<b>Test options</b> .....	<b>60</b>
<b>H.3</b>	<b>PRD test</b> .....	<b>60</b>
<b>H.4</b>	<b>Vent test</b> .....	<b>61</b>
<b>H.5</b>	<b>System assessment</b> .....	<b>61</b>
<b>H.5.1</b>	<b>Qualification limit envelope</b> .....	<b>61</b>
<b>H.5.2</b>	<b>Service limit envelope</b> .....	<b>61</b>
<b>H.5.3</b>	<b>Acceptable results</b> .....	<b>61</b>
<b>H.6</b>	<b>Generation of a safety envelope and actual cylinder/PRD performance</b> .....	<b>61</b>
<b>Annex I</b>	<b>(informative) Information of factor of safety</b> .....	<b>63</b>
<b>I.1</b>	<b>Purpose</b> .....	<b>63</b>
<b>I.2</b>	<b>Background</b> .....	<b>63</b>
<b>I.3</b>	<b>Recommended safety factor</b> .....	<b>63</b>
<b>I.4</b>	<b>Discussion</b> .....	<b>63</b>

<b>I.5</b>	<b>Conclusions .....</b>	<b>65</b>
<b>I.6</b>	<b>Recommendations.....</b>	<b>65</b>
<b>I.7</b>	<b>Further reading.....</b>	<b>65</b>
	<b>Bibliography .....</b>	<b>66</b>