

# ISO 10464:2004-08 (E)

## Gas cylinders - Refillable welded steel cylinders for liquefied petroleum gas (LPG) - Periodic inspection and testing

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Intervals between periodic inspections .....</b>	<b>2</b>
<b>5</b>	<b>Procedures for periodic inspection .....</b>	<b>2</b>
<b>5.1</b>	<b>General .....</b>	<b>2</b>
<b>5.2</b>	<b>Test procedures .....</b>	<b>3</b>
<b>5.3</b>	<b>External visual inspection .....</b>	<b>3</b>
<b>5.4</b>	<b>Additional test procedures .....</b>	<b>6</b>
<b>6</b>	<b>Inspection of cylinder threads .....</b>	<b>9</b>
<b>6.1</b>	<b>General .....</b>	<b>9</b>
<b>6.2</b>	<b>Internal threads .....</b>	<b>9</b>
<b>6.3</b>	<b>External threads .....</b>	<b>9</b>
<b>6.4</b>	<b>Damaged threads .....</b>	<b>9</b>
<b>7</b>	<b>Final operations .....</b>	<b>9</b>
<b>7.1</b>	<b>Drying .....</b>	<b>9</b>
<b>7.2</b>	<b>Purging .....</b>	<b>10</b>
<b>7.3</b>	<b>Tare mass .....</b>	<b>10</b>
<b>7.4</b>	<b>Valving .....</b>	<b>10</b>
<b>7.5</b>	<b>Marking .....</b>	<b>10</b>
<b>7.6</b>	<b>Reference to next periodic inspection date .....</b>	<b>10</b>
<b>7.7</b>	<b>Identification of contents .....</b>	<b>10</b>
<b>8</b>	<b>Rendering cylinders unserviceable .....</b>	<b>10</b>
<b>9</b>	<b>Records .....</b>	<b>11</b>
<b>Annex A (normative) Requirements for 15-year periodic inspection interval .....</b>		<b>12</b>
<b>Annex B (informative) System of protection against external corrosion .....</b>		<b>13</b>
<b>Annex C (informative) Procedure that may be adopted when it is suspected that a cylinder valve is obstructed/blocked .....</b>		<b>14</b>
<b>Bibliography .....</b>		<b>15</b>