DIN EN 12817:2006-06 (E)

LPG equipment and accessories - Inspection and requalification of LP G tanks up to and including 13 m<(hoch)3> overground

Contents

Page

Introduction 5

1 Scope 5

2 Terms and definitions 5

3 Safety 6
3.1 Safety precautions 6
3.2 Unsafe conditions 6
3.3 Leaks 6

4 Written scheme 6

5 Tank inspection and re-qualification 7
5.1 Routine inspection 7
5.2 Periodic inspection 7
5.3 Re-qualification 7

6 Inspection of tank and tank fittings 8
6.1 Tank 8
6.2 Tank fittings and immediate pipework 8
6.3 Valve cover 9
6.4 Bonding 9
6.5 Pressure relief valve 9
6.6 Pressure gauge 9
6.7 Contents gauges 9
6.8 Shut-off valves 9
6.9 Studs, bolts, nuts, and washers 9

7 Site inspection 10
7.1 Storage site 10
7.2 Piers and foundations 10
7.3 Warning notices 10

8 Competence 10
8.1 Routine inspection 10
8.2 Periodic inspection 10
8.3 Re-qualification 10

9 Records 10
9.1 Tank data 10
9.2 Reports 11

Annex A (informative) Visual inspection 12

A.1 Internal and external visual inspections 12
A.2 Inspection techniques 12
A.2.1 External inspection 12
A.2.2 Internal inspection 12
A.3 Records 12
A.4 Additional inspection 12

Annex B (informative) Hydraulic pressure test 14

Annex C (informative) Acoustic emission examination during proof testing 15

C.1 General 15
C.2 Safety precautions 15
C.3 Acceptance criteria 16

Annex D (informative) Ultrasonic thickness test 17

D.1 General 17
D.2 Apparatus setting 17
D.3 Control measurement 17
D.4 Shell thickness measurements 17
D.5 End thickness 17
D.6 Interpretation 17
D.7 Rejection criteria 18

Annex E (informative) Assessment of tanks by sampling 19

E.1 General 19
E.2 Homogeneous batch 19
E.3 Selection of samples 19
E.4 Sample selection 20
E.5 Inspection period 20
E.6 Presentation of results and decisions 20
E.7 Pass criteria 20
E.8 Example calculation of a sample 20

Annex F (informative) Example of a report 22

Annex ZA (informative) A-deviations 23