

# ISO 29802:2009-11 (E)

## All terrain (AT) tyres and rims - Symbol marked pneumatic tyres on 5 degrees tapered rims - Designation, dimension, marking and load ratings

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Tyre size designations .....	2
4.1	Dimensional and constructional characteristics .....	2
4.2	Service condition .....	3
4.3	Other service characteristics .....	4
5	Marking .....	4
6	Tyre dimensions .....	5
6.1	General .....	5
6.2	Calculation of design tyre dimensions .....	5
6.3	Calculation of "maximum overall tyre dimensions" .....	6
6.4	Calculation of "maximum overall grown tyre dimensions" .....	6
6.5	Calculation of "minimum tyre dimensions" .....	7
6.6	Range of approved rim widths .....	8
7	Method of measurement of tyre dimensions .....	8
8	Reference load-carrying capacity .....	9
9	Load ratings .....	9
10	Inflation pressures .....	9
11	Rims .....	10
11.1	Designation and marking .....	10
11.2	Rim contours .....	10
11.3	Rim diameter and hump circumference .....	11
12	Valve hole .....	12
12.1	General .....	12
12.2	Snap-in valves .....	12