

# ISO 4209-2:2012-09 (E)

## Truck and bus tyres and rims (metric series) - Part 2: Rims

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Designation and marking .....</b>	<b>1</b>
<b>5</b>	<b>5° tapered (drop-centre) rims .....</b>	<b>1</b>
<b>5.1</b>	<b>Rimflange .....</b>	<b>1</b>
<b>5.2</b>	<b>Rim contours .....</b>	<b>1</b>
<b>5.3</b>	<b>Rim diameter and hump circumference .....</b>	<b>4</b>
<b>5.4</b>	<b>Valve holes .....</b>	<b>4</b>
<b>6</b>	<b>15° tapered (drop-centre) rims .....</b>	<b>6</b>
<b>6.1</b>	<b>Rim contours .....</b>	<b>6</b>
<b>6.2</b>	<b>Rim diameters .....</b>	<b>8</b>
<b>6.3</b>	<b>Valve holes .....</b>	<b>9</b>
<b>Bibliography .....</b>		<b>11</b>