

# ISO 5892:2013-06 (E)

## Rubber building gaskets - Materials for preformed solid vulcanized structural gaskets - Specification

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Types of material .....</b>	<b>2</b>
<b>5</b>	<b>Working temperature range .....</b>	<b>2</b>
<b>6</b>	<b>Material and workmanship .....</b>	<b>2</b>
<b>7</b>	<b>Dimensions and tolerances .....</b>	<b>2</b>
<b>8</b>	<b>General requirements .....</b>	<b>2</b>
<b>8.1</b>	<b>Test pieces .....</b>	<b>2</b>
<b>8.2</b>	<b>Hardness .....</b>	<b>3</b>
<b>8.3</b>	<b>Tensile strength and elongation at break .....</b>	<b>3</b>
<b>8.4</b>	<b>Compression set .....</b>	<b>3</b>
<b>8.5</b>	<b>Accelerated ageing .....</b>	<b>3</b>
<b>8.6</b>	<b>Ozone resistance .....</b>	<b>3</b>
<b>9</b>	<b>Specific requirements .....</b>	<b>4</b>
<b>9.1</b>	<b>General .....</b>	<b>4</b>
<b>9.2</b>	<b>High-density ozone resistance .....</b>	<b>4</b>
<b>9.3</b>	<b>Holding force .....</b>	<b>4</b>
<b>9.4</b>	<b>Watertightness .....</b>	<b>4</b>
<b>9.5</b>	<b>Flammability .....</b>	<b>4</b>
<b>9.6</b>	<b>Contact and migration staining .....</b>	<b>4</b>
<b>9.7</b>	<b>Low-temperature brittleness .....</b>	<b>4</b>
<b>9.8</b>	<b>Low-temperature compression set .....</b>	<b>4</b>
<b>Annex A (informative)</b>	<b>Holding force test .....</b>	<b>6</b>
<b>Bibliography .....</b>		<b>9</b>