

# ISO 9563:2015-09 (E)

## Belt drives - Electrical conductivity of antistatic endless synchronous belts - Characteristics and test method

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Electricalresistance--specification .....</b>	<b>1</b>
<b>3.1</b>	<b>General .....</b>	<b>1</b>
<b>3.2</b>	<b>Resistance value .....</b>	<b>2</b>
<b>3.3</b>	<b>Minimum value of electrical resistance .....</b>	<b>2</b>
<b>4</b>	<b>Selection and preparation of belts for test .....</b>	<b>2</b>
<b>4.1</b>	<b>Laboratory test .....</b>	<b>2</b>
<b>4.2</b>	<b>Production test .....</b>	<b>2</b>
<b>5</b>	<b>Test method .....</b>	<b>3</b>
<b>5.1</b>	<b>Apparatus -- insulation tester .....</b>	<b>3</b>
<b>5.2</b>	<b>Electrodes and contacts for laboratory and production tests .....</b>	<b>3</b>
<b>5.3</b>	<b>Test procedures .....</b>	<b>3</b>
<b>5.3.1</b>	<b>Laboratory test .....</b>	<b>3</b>
<b>5.3.2</b>	<b>Production test .....</b>	<b>3</b>
<b>5.3.3</b>	<b>Test timing .....</b>	<b>3</b>
<b>5.3.4</b>	<b>Interpretation of results .....</b>	<b>3</b>
<b>Annex A (informative)</b>	<b>Electrical conductive coating .....</b>	<b>5</b>
<b>Bibliography .....</b>		<b>6</b>