ISO 4642-2:2015-12 (E)

Rubber and plastics hoses, non-collapsible, for fire-fighting service - Part 2: Semi-rigid hoses (and hose assemblies) for pumps and vehicles

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Classification 2
4.1 General 2
4.2 Classification by types (hose construction) 2
4.3 Classification by class (materials for lining and cover) 2
4.4 Classification by category 3

5 Dimensions, tolerances and maximum mass 3
5.1 Inside diameter and maximum mass 3
5.2 Length and tolerances on length 3
5.3 Concentricity 4

6 Performance requirements of finished hose 4
6.1 Hydrostatic requirements 4
6.1.1 Deformation under maximum working pressure 4
6.1.2 Deformation under proof pressure 4
6.1.3 Minimum burst pressure 4
6.1.4 Kink pressure 4
6.2 Adhesion 4
6.3 Accelerated ageing 5
6.4 Abrasion resistance 5
6.4.1 General 5
6.4.2 Abrasion resistance of class 5 and class 6 hoses 5
6.4.3 Abrasion resistance of classes 1, 2, 3 and 4 hoses 5
6.5 Low temperature flexibility 5
6.6 Hot surface resistance 5
6.7 Ozone resistance 6
6.8 Bending and crush resistance 6
6.9 UV resistance (xenon arc lamp) 6
6.10 Loss in mass on heating 6
6.11 Deformation under crushing (type C only) 6
6.12 Hose assemblies 6

7 Frequency of testing 6

8 Type tests 7

9 Test report 7

10 Recommendation for packaging and storage 7

11 Marking 7

Annex A (normative) Kink pressure test **8**

Annex B (normative) Accelerated ageing test **9**

Annex C (normative) Surface abrasion resistance test **10**

Annex D (normative) Point abrasion resistance test **12**

Annex E (normative) Hot surface resistance test **15**

Annex F (normative) Bending and crush resistance test **20**

Annex G (normative) Deformation under crushing test **22**

Annex H (normative) Adhesion test (lay-flat fire-fighting hoses) **24**

Annex I (normative) Test for fire-fighting hose assemblies **26**

Annex J (normative) Type test and routine test **27**

Annex K (informative) Production tests **28**

Bibliography **29**