

DIN EN 1762:2017-06 (E)

Rubber hoses and hose assemblies for liquefied petroleum gas, LPG (liquid or gaseous phase), and natural gas up to 25 bar (2,5 MPa) - Specification

Contents	Page
European foreword	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 Classification	6
5 Materials and construction	7
5.1 Hose	7
5.2 Hose assemblies	7
6 Dimensions	7
6.1 Nominal bore, internal diameters, outside diameters, tolerances, and minimum bend radius	7
Table 1 -- Dimensions and tolerances of hoses of types D and D-LT	8
Table 2 -- Dimensions and tolerances of hoses of types SD, SD-LTS and SD-LTR	9
6.2 Minimum thickness of lining and cover	9
6.3 Concentricity	9
6.4 Tolerances on length	9
7 Physical properties	10
7.1 Rubber Compounds	10
Table 3 -- Physical properties of compounds	10
7.2 Finished hose and hose assemblies	11
Table 4 -- Physical properties of finished hose and hose assemblies	11
8 Electrical properties	12
8.1 General	12
8.2 Textile reinforced hoses with bonding wires	12
8.3 Textile reinforced hoses with conducting materials	13
8.4 Wire helix reinforced hoses	13
8.4.1 Grade M-hoses (see 8.2)	13
8.4.2 Grade -hoses (see 8.3)	13
8.5 Hose assemblies that are required to be discontinuous	13
9 Type testing	13
10 Frequency of testing	13
11 Marking	14
11.1 Hoses	14
11.2 Hose assemblies	14
Annex A (normative) Flammability test	15

A.1	Method	15
A.2	Assessment	15
Figure A.1 -- Arrangement for flammability test		16
Annex B (normative) Test frequency		17
Table B.1 -- Type and routine tests		17
Annex C (informative) Test frequency		19
Table C.1 -- Recommended test frequency (Production acceptance tests)		19