DIN EN 1762:2017-06 (E)

Rubber hoses and hose assemblies for liquefied petroleum gas, LPG (liquid or gaseous phase), and natural gas up to 25 bar (2,5 MPa) - Specif ication

Contents

Page

European foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Classification 6

5 Materials and construction 7
5.1 Hose 7
5.2 Hose assemblies 7

6 Dimensions 7
6.1 Nominal bore, internal diameters, outside diameters, tolerances, and minimum bend radius 7

Table 1 -- Dimensions and tolerances of hoses of types D and D-LT 8

Table 2 -- Dimensions and tolerances of hoses of types SD, SD-LTS and SD-LTR 9
6.2 Minimum thickness of lining and cover 9
6.3 Concentricity 9
6.4 Tolerances on length 9

7 Physical properties 10
7.1 Rubber Compounds 10

Table 3 -- Physical properties of compounds 10
7.2 Finished hose and hose assemblies 11

Table 4 -- Physical properties of finished hose and hose assemblies 11

8 Electrical properties 12
8.1 General 12
8.2 Textile reinforced hoses with bonding wires 12
8.3 Textile reinforced hoses with conducting materials 13
8.4 Wire helix reinforced hoses 13
8.4.1 Grade M-hoses (see 8.2) 13
8.4.2 Grade -hoses (see 8.3) 13
8.5 Hose assemblies that are required to be discontinuous 13

9 Type testing 13

10 Frequency of testing 13

11 Marking 14
11.1 Hoses 14
11.2 Hose assemblies 14

Annex A (normative) Flammability test 15

A.1 Method 15
A.2 Assessment 15

Figure A.1 -- Arrangement for flammability test 16

Annex B (normative) Test frequency 17

Table B.1 -- Type and routine tests 17

Annex C (informative) Test frequency 19

Table C.1 -- Recommended test frequency (Production acceptance tests) 19