

# ISO 18804:2017-10 (E)

## Rims for agricultural, forestry and construction machines

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Rim diameter and circumferences .....</b>	<b>1</b>
<b>5</b>	<b>Rim contours and valve holes .....</b>	<b>3</b>
<b>5.1</b>	<b>Drop-centre W, DW and TW rims .....</b>	<b>3</b>
<b>5.2</b>	<b>Drop-centre DH rims .....</b>	<b>7</b>
<b>5.3</b>	<b>Drop-centre MW rims .....</b>	<b>9</b>
<b>5.4</b>	<b>Drop-centre DD rims .....</b>	<b>11</b>
<b>5.5</b>	<b>Other drop-centre rims .....</b>	<b>11</b>
<b>5.6</b>	<b>Semi-drop-centre rims (multi-piece) .....</b>	<b>14</b>
<b>5.7</b>	<b>Divided rims .....</b>	<b>16</b>
<b>5.8</b>	<b>5° and 3° flat base rims (multi-piece) -- DWM, VF and HF .....</b>	<b>16</b>
<b>5.9</b>	<b>Full tapered bead seat rims (multi-piece) -- TH .....</b>	<b>18</b>
<b>5.10</b>	<b>AG 15° drop-centre rims .....</b>	<b>19</b>
<b>6</b>	<b>Rim knurling .....</b>	<b>21</b>
<b>Annex A (normative) Rim diameter measurements .....</b>		<b>22</b>
<b>Annex B (informative) 5° drop-centre rims with nominal diameter codes 15.3 and 16.1 .....</b>		<b>24</b>
<b>Annex C (informative) 15° drop-centre rims with nominal diameter code 15.5, 16.5, and 17.5 .....</b>		<b>26</b>
<b>Bibliography .....</b>		<b>28</b>