

ISO/TS 21396:2017-12 (E)

Rubber - Determination of mass concentration of tire and road wear particles (TRWP) in soil and sediments - Pyrolysis-GC/MS method

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Reagents	2
6 Apparatus	3
7 Specimen preparation laboratory	5
8 Measuring range	5
9 Limit of detection	5
10 Procedure	6
10.1 General	6
10.2 Sample collection	6
10.3 Deuterated internal standard preparation	6
10.4 Calibration curve preparation	7
10.4.1 Stock solutions	7
10.4.2 Calibration curves	7
10.5 Sample preparation	8
10.5.1 Oven drying	8
10.5.2 Sieving and homogenization	8
10.6 Sample measurement	8
10.6.1 Sample mass	8
10.6.2 Internal standard addition	9
10.6.3 Pyrolysis-gas chromatograph/mass spectrometer measurement	9
11 Analysis	9
11.1 TRWP detection limit	9
11.2 Quantity of tyre polymer in the sample	9
11.3 Mass concentration of TRWP	10
12 Performance characteristics	10
12.1 General	10
12.2 Specific performance characteristics	10
12.3 Method detection limit	10
13 Test report	10
Annex A (informative) Recipe for calibration curves and stock solutions	12

Annex B (informative) Curie-point pyrolyser	14
Annex C (informative) Representative calibration curves and pyrograms	15
Annex D (normative) Calculation of TRWP detection limits	20
Annex E (normative) Calculation of results using dimer markers	21
Bibliography	23