# ISO/TS 21396:2017-12 (E)

## Rubber - Determination of mass concentration of tire and road wear particles (TRWP) in soil and sediments - Pyrolysis-GC/MS method

## Contents

Page


Foreword ..... iv

Introduction ..... v

1 Scope ..... 1

2 Normative references ..... 1

3 Termsanddefinitions ..... 1

4 Principle ..... 2

5 Reagents ..... 2

6 Apparatus ..... 3

7 Specimen preparation laboratory ..... 5

8 Measuring range ..... 5

9 Limit of detection ..... 5

10 Procedure ..... 6
10.1 General ..... 6
10.2 Sample collection ..... 6
10.3 Deuterated internal standard preparation ..... 6
10.4 Calibration curve preparation ..... 7
10.4.1 Stock solutions ..... 7
10.4.2 Calibration curves ..... 7
10.5 Sample preparation ..... 8
10.5.1 Oven drying ..... 8
10.5.2 Sieving and homogenization ..... 8
10.6 Sample measurement ..... 8
10.6.1 Sample mass ..... 8
10.6.2 Internal standard addition ..... 9
10.6.3 Pyrolysis-gas chromatograph/mass spectrometer measurement ..... 9

11 Analysis ..... 9
11.1 TRWP detection limit ..... 9
11.2 Quantity of tyre polymer in the sample ..... 9
11.3 Mass concentration of TRWP ..... 10

12 Performance characteristics ..... 10
12.1 General ..... 10
12.2 Specific performance characteristics ..... 10
12.3 Method detection limit ..... 10

13 Test report ..... 10

Annex A (informative) Recipe for calibration curves and stock solutions ..... 12

**Annex B (informative) Curie-point pyrolyser ..... 14**

**Annex C (informative) Representative calibration curves and pyrograms ..... 15**

**Annex D (normative) Calculation of TRWP detection limits ..... 20**

**Annex E (normative) Calculation of results using dimer markers ..... 21**

**Bibliography ..... 23**