ISO 21342:2019 (E)

Synchronous belt drives — Automotive belts and pulleys

Contents

Foreword

1 Scope

2 Normative reference

3 Terms and definitions

4 Profiles

5 Belt designation

6 Belt dimensions and tolerances

- 6.1 Belt tooth dimensions — Trapezoidal tooth belts of types ZA and ZB
- 6.2 Belt tooth dimensions — Curvilinear tooth belts of types ZH and YH
- 6.3 Belt tooth dimensions — Curvilinear tooth belts of types YR and ZR
- 6.4 Belt tooth dimensions — Curvilinear tooth belts of types YS and ZS
- 6.5 Belt pitch length and tolerances
- 6.6 Belt widths and tolerances

7 Pitch length measurement

- 7.1 Measuring fixture
- 7.2 Total measuring force
- 7.3 Procedure
- 7.4 Dimensions and clearance between measuring pulley and belt, and measuring pulley grooves

8 Lateral runout measurement

- 8.1 Fixture
- 8.1.1 Belt
- 8.1.2 Pulleys
- 8.2 Measuring device
- 8.3 Procedure
- 8.4 Results

9 Pulley types

10 Pulley designation

11 Pulley groove profile

- 11.1 Pulleys of types ZA and ZB (involute groove profile)
- 11.2 Pulleys of types ZH and YH
- 11.3 Pulleys of types ZR and YR
- 11.4 Pulleys of types ZS and YS

12 Pulley dimensions and tolerances

- 12.1 Pitch tolerances
- 12.2 Pulley outside diameter tolerances
- 12.3 Minimum pulley width
- 12.4 Flange dimensions
- 12.5 Other pulley tolerances
- 12.5.1 Axial runout
- 12.5.2 Radial runout
- 12.5.3 Parallelism
- 12.5.4 Taper

13 Quality specification