

# ISO 20910:2019 (E)

## Coding for radio frequency identification (RFID) tyre tags

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
|         | Introduction                                    |
| 1       | Scope   |
| 2       | Normative references                            |
| 3       | Terms and definitions                           |
| 4       | General requirements                            |
| 4.1     | Memory banks and data structure organization    |
| 4.2     | UII memory bank (MB01)                          |
| 4.3     | RFID technical specification                    |
| 4.3.1   | UII memory bank MB01 size                       |
| 4.3.2   | Security/Locking data (Permalock command)       |
| 4.3.3   | Numbering system identifier                     |
| 5       | Memory banks                                    |
| 5.1     | MB00 (Reserved memory bank)                     |
| 5.2     | MB01 (UII memory bank)                          |
| 5.3     | MB10 (TID memory bank)                          |
| 5.4     | MB11 (User memory bank)                         |
| 6       | Data structure for unique item identifier (UII) |
| Annex A | (informative) Data scheme for tyre RFID tag     |
| A.1     | Tag memory mapping                              |
| A.2     | Main mandatory and optional commands            |
| A.2.1   | Basic operations                                |
| A.2.2   | Access commands (OPEN or SECURED state)         |

Page count: 12