

# ISO 9982:2021-09 (E)

## Belt drives - Pulleys and V-ribbed belts for industrial applications - PH, PJ, PK, PL and PM profiles: dimensions

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols .....</b>	<b>1</b>
<b>5</b>	<b>Pulleys .....</b>	<b>2</b>
<b>5.1</b>	<b>Groove dimensions and tolerances .....</b>	<b>2</b>
<b>5.2</b>	<b>Minimum effective diameter .....</b>	<b>5</b>
<b>5.3</b>	<b>Tolerances on finished pulley .....</b>	<b>5</b>
<b>5.3.1</b>	<b>Checking conditions .....</b>	<b>5</b>
<b>5.3.2</b>	<b>Groove-to-groove diameter tolerances .....</b>	<b>5</b>
<b>5.3.3</b>	<b>Radial circular run-out .....</b>	<b>5</b>
<b>5.3.4</b>	<b>Axial circular run-out .....</b>	<b>6</b>
<b>5.3.5</b>	<b>Diameter over balls .....</b>	<b>6</b>
<b>5.3.6</b>	<b>Groove finish .....</b>	<b>6</b>
<b>5.4</b>	<b>Pitch diameter, <math>d_p</math> .....</b>	<b>6</b>
<b>5.5</b>	<b>Designation of pulleys .....</b>	<b>7</b>
<b>6</b>	<b>Belts .....</b>	<b>7</b>
<b>6.1</b>	<b>Belt dimensions .....</b>	<b>7</b>
<b>6.2</b>	<b>Measurement of effective belt length .....</b>	<b>9</b>
<b>6.2.1</b>	<b>Measuring fixture -- Apparatus .....</b>	<b>9</b>
<b>6.2.2</b>	<b>Measuring force .....</b>	<b>9</b>
<b>6.2.3</b>	<b>Procedure .....</b>	<b>9</b>
<b>6.2.4</b>	<b>Manufacturing tolerances .....</b>	<b>10</b>
<b>6.3</b>	<b>Measurement of centre distance variation .....</b>	<b>11</b>
<b>6.4</b>	<b>Designation of belts .....</b>	<b>11</b>
Bibliography .....		13