

# DIN 7865-2:2022-08 (E)

## Elastomeric-Waterstops for sealing joints in concrete - Part 2: Material specifications and testing

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b> <b>Scope</b> .....		<b>4</b>
<b>2</b> <b>Normative references</b> .....		<b>4</b>
<b>3</b> <b>Terms and definitions</b> .....		<b>5</b>
<b>4</b> <b>Waterstop joints and jointing techniques</b> .....		<b>5</b>
4.1 <b>General</b> .....		<b>5</b>
4.2 <b>Elastomer waterstops with steel strips</b> .....		<b>6</b>
4.3 <b>Elastomer capping joint waterstop</b> .....		<b>6</b>
<b>5</b> <b>Requirements</b> .....		<b>6</b>
5.1 <b>Properties</b> .....		<b>6</b>
5.2 <b>Rubber-to-metal adhesion</b> .....		<b>7</b>
5.3 <b>Behaviour after conditioning in hot bitumen</b> .....		<b>7</b>
<b>6</b> <b>Testing</b> .....		<b>7</b>
6.1 <b>Test piece preparation</b> .....		<b>7</b>
6.2 <b>Shore hardness</b> .....		<b>8</b>
6.3 <b>Tensile strength at break and elongation at break</b> .....		<b>8</b>
6.4 <b>Compression set</b> .....		<b>8</b>
6.5 <b>Tear strength</b> .....		<b>8</b>
6.6 <b>Behaviour after heat ageing</b> .....		<b>8</b>
6.7 <b>Change in hardness after cold storage</b> .....		<b>8</b>
6.8 <b>Tension set</b> .....		<b>8</b>
6.9 <b>Rubber-to-metal adhesion</b> .....		<b>8</b>
6.10 <b>Behaviour after conditioning in hot bitumen</b> .....		<b>9</b>
6.11 <b>Behaviour after ozone ageing</b> .....		<b>10</b>
6.12 <b>Bond strength</b> .....		<b>10</b>
<b>7</b> <b>Marking</b> .....		<b>11</b>

## Figures

Figure 1 — Test piece .....	9
Figure 2 — Test container dimensions .....	10

## Tables

Table 1 — Requirements.....	6
-----------------------------	---