

ISO 3739-1:2022-10 (E)

Industrial tyres and rims - Part 1: Pneumatic tyres (metric series) on 5 degrees tapered or flat base rims - Designation, dimensions and marking

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Tyre designations	1
4.1	Dimensional and constructional characteristics	1
4.1.1	General	1
4.1.2	Nominal section width	2
4.1.3	Nominal aspect ratio	2
4.1.4	Tyre construction code	2
4.1.5	Nominal rim diameter code	2
4.2	Service description	2
4.2.1	General	2
4.2.2	Load index	3
4.2.3	Speed symbol	4
4.3	Other service characteristics	5
5	Marking	5
5.1	General marking	5
5.2	Maximum speed marking	5
6	Tyre dimensions	6
6.1	General	6
6.2	Calculation of design tyre dimensions	6
6.2.1	Nominal aspect ratio, AR	6
6.2.2	Theoretical rim width, Rth	6
6.2.3	Design tyre section width, S	6
6.2.4	Design tyre section height, H	6
6.2.5	Design tyre overall diameter, DO	6
6.3	Calculation of maximum overall tyre dimensions in service	6
6.3.1	General	6
6.3.2	Maximum overall width in service, Wmax	7
6.3.3	Maximum overall diameter in service, DO,max	7
7	Design tyre dimensions	7
8	Tyre size combinations	8
9	Method of measurement of tyre dimensions	9
Annex A (informative) Tyre size designation		10
Bibliography		14